

# DIN 75201:2024-06 (E)

## Determination of the fogging characteristics of trim materials in the interior of automobiles

---

<b>Contents</b>		<b>Page</b>
Foreword .....		4
1	Scope .....	6
2	Normative references .....	6
3	Terms and definitions .....	6
4	Tolerances .....	7
5	Principle of methods .....	7
5.1	Method A .....	7
5.2	Method B .....	7
6	Designation .....	8
6.1	Method A .....	8
6.2	Method B .....	8
7	Materials, auxiliary equipment, apparatus .....	8
7.1	Materials .....	8
7.2	Auxiliary equipment .....	9
7.3	Apparatus .....	10
8	Sampling, test specimens and conditioning .....	15
8.1	Number of test specimens .....	15
8.1.1	Method A .....	15
8.1.2	Method B .....	15
8.2	Sampling and conditioning .....	15
8.2.1	General .....	15
8.2.2	Coated and uncoated textiles .....	15
8.2.3	Leather .....	15
8.2.4	Raw materials in powder, paste and liquid form .....	15
8.2.5	Moulded parts .....	15
8.3	Drying test specimens .....	16
9	Procedure .....	16
9.1	Cleaning .....	16
9.1.1	Fluoroelastomer sealing rings .....	16
9.1.2	Beakers and metal rings .....	16
9.1.3	Glass plates for method A .....	17
9.1.4	Inspection after cleaning .....	17
9.1.5	Glass plates for method B .....	18
9.2	Control test with DIDP .....	18
9.2.1	Control test for method A .....	18
9.2.2	Control test for method B .....	18
9.3	Arrangement of test specimens .....	18
9.4	Measurements to be taken before the fogging test .....	18
9.4.1	Method A: Gloss values .....	18
9.4.2	Method B: Aluminium foils .....	19
10	Fogging test .....	19

10.1	Covering the glass beakers .....	19
10.1.1	Method A .....	19
10.1.2	Method B .....	19
10.2	Conditions for the tempering unit .....	19
10.3	Conditioning requirements .....	20
10.3.1	Method A .....	20
10.3.2	Method B .....	20
10.4	Measurements to be taken after the fogging test .....	20
10.4.1	Method A .....	20
10.4.2	Method B .....	20
10.4.3	Number of measurements .....	20
11	Evaluation .....	21
11.1	Method A .....	21
11.2	Method B .....	22
12	Test report .....	23
12.1	Method A .....	23
12.2	Method B .....	24
	Annex A (informative) Explanatory notes .....	25
	Bibliography .....	26
	Figures Figure 1 -- Glass beaker, top illustration = side view, bottom illustration = view from above .	9
	Figure 2 -- Tempering unit (design example thermostatically controlled bath) .....	11
	Figure 3 -- Tempering unit -- Accessory (design example dry tempering unit) .....	12
	Figure 4 -- Tempering unit (design example dry tempering unit) .....	13
	Figure 5 -- Backing plate with glass plate and spacer, with example showing reference marks for positioning and centring the glossmeter (e.g. rectangular (can also be round with concentric hole)) .....	14
	Tables Table 1 -- Duration of drying for various materials .....	16