DIN EN 1254-3:2025-04 (E)

Copper and copper alloys - Plumbing fittings - Part 3: Compression fittings for use with plastics and multilayer pipes (includes Amendment A1:2025)

Contents

Page

European foreword 4

Introduction 6

1 Scope 7

2 Normative references 8

3 Terms and definitions 10

4 Product characteristics 10
4.1 Internal pressure 10
4.2 Tightness 10
4.3 Resistance to high temperature for fittings with elastomeric seals (for heating networks) 11
4.4 Release of dangerous substances 11
4.5 Durability 12
4.6 Wall thickness at the threaded portions of fittings and/or compression nut 12
4.7 Dimensions of tail pipe ends for swivel fittings 12
4.8 Dimensions of gas union connectors 13
4.9 Threaded end dimensions 13
4.10 Other adapter ends (not defined in [A1] EN 1254-20:2021+A1:2025 [A1]) 13
4.11 Bore dimensions 13
4.12 Identity of elastomeric sealing material for liquid applications 13
4.13 Identity of elastomeric sealing material for gas applications 13
4.14 Pipe abutment 14
4.15 Alignment of the fitting ends 14
4.16 Shapes for tightening systems 14
4.17 Surface condition 14
4.18 Plated or coated surfaces 14
4.19 [A1] Wall thickness of the fitting body [A1] 14

5 Testing, assessment and sampling methods 14
5.1 General 14
5.2 Internal pressure 15
5.3 Tightness 16
5.4 Durability 20
5.5 Wall thickness at threaded portions of adaptor fittings 20
5.6 Dimensions of tail pipe ends for swivel fittings 21
5.7 Dimensions of gas union connectors 21
5.8 Threaded end dimensions 21
5.9 Bore dimensions 21
5.10 Identity of elastomeric sealing material for liquid applications 21
5.11 Identity of elastomeric sealing material for gas applications 21
5.12 Alignment of the fitting ends 21
5.13 [A1] Wall thickness of the fitting body [A1] 22

6 Evaluation of conformity 22
6.1 General 22
6.2 Type testing 22
6.3 Factory production control (FPC) 28

7 Designation **31**

8 Marking, labelling and packaging **31**
8.1 General **31**
8.2 Additional marking **31**
8.3 Dezincification resistant copper zinc alloys **32**

Annex A (normative) Operating temperatures and design pressures **33**

Bibliography **35**