

# ISO 11357-6:2025-06 (E)

## Plastics - Differential scanning calorimetry (DSC) - Part 6: Determination of oxidation induction time (isothermal OIT) and oxidation induction temperature (dynamic OIT)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Principle .....	2
4.1	General .....	2
4.2	Oxidation induction time (isothermal OIT) .....	2
4.3	Oxidation induction temperature (dynamic OIT) .....	2
5	Apparatus and materials .....	2
5.1	General .....	2
5.2	DSC instrument .....	3
5.3	Crucibles .....	3
5.4	Flowmeter .....	3
5.5	Oxygen .....	3
5.6	Air .....	3
5.7	Nitrogen .....	3
5.8	Gas-selector switch and regulators .....	3
6	Test specimens .....	4
6.1	General .....	4
6.2	Specimens from compression-moulded plates .....	4
6.3	Specimens from injection-moulded plates or melt flow extrudates .....	4
6.4	Specimens from finished parts .....	4
7	Test conditions and specimen conditioning .....	5
8	Calibration .....	5
8.1	Oxidation induction time (isothermal OIT) .....	5
8.1.1	General .....	5
8.1.2	Dynamic temperature calibration .....	5
8.1.3	Isothermal stepwise temperature calibration .....	5
8.2	Oxidation induction temperature (dynamic OIT) .....	5
9	Procedure .....	6
9.1	Setting up the instrument .....	6
9.2	Loading the test specimen into the crucible .....	6
9.3	Insertion of crucibles .....	6
9.4	Nitrogen, air and oxygen flow .....	6
9.5	Sensitivity adjustment .....	6
9.6	Performance of measurement .....	6
9.6.1	Oxidation induction time (isothermal OIT) .....	6
9.6.2	Oxidation induction temperature (dynamic OIT) .....	7
9.7	Cleaning .....	8
10	Expression of results .....	8
11	Precision and bias .....	10
12	Test report .....	10
Bibliography .....		12