

DIN EN 1555-2:2026-02 (E)

Plastics piping systems for the supply of gaseous fuels - Polyethylene (PE) - Part 2: Pipes

Contents		Page
European foreword		4
Introduction		6
1	Scope	7
2	Normative references	7
3	Terms and definitions	8
3.1	Terms related to geometry	9
3.2	Terms related to material	10
3.3	Terms related to joints	11
4	Symbols and abbreviated terms	11
4.1	Symbols	11
4.2	Abbreviated terms	12
5	Material	12
5.1	Compound for pipes	12
5.2	Compound for identification stripes	13
5.3	External reworked material and recycle	13
6	General characteristics	13
6.1	Appearance	13
6.2	Colour	13
7	Geometrical characteristics	14
7.1	Measurement of dimensions	14
7.2	Mean outside diameters, out-of-roundness (ovality) and tolerances	14
7.3	Wall thicknesses and related tolerances	15
7.3.1	Minimum wall thicknesses	15
7.3.2	Tolerance on the wall thicknesses	17
7.4	Coiled pipe	18
7.5	Lengths	18
8	Mechanical characteristics	19
8.1	Conditioning	19
8.2	Requirements	19
9	Physical characteristics	24
9.1	Conditioning	24
9.2	Requirements	24
9.3	Circumferential reversion of pipes with dn 250 mm	25
10	Performance requirements	26
11	Marking	26
11.1	General	26
11.2	Minimum required marking	26
11.3	Additional marking	27

Annex A (normative) Pipes with co-extruded layers	28
A.1 General	28
A.2 Material	28
A.3 Geometrical characteristics	28
A.4 Mechanical characteristics	28
A.5 Physical characteristics	28
A.6 Marking	28
A.7 Delamination	29
A.8 Integrity of the structure	29
Annex B (normative) Pipes with peelable layer	30
B.1 General	30
B.2 Geometrical characteristics	30
B.3 Mechanical characteristics	30
B.4 Physical characteristics	30
B.5 Peelable layer adhesion	30
B.6 Marking	30
Annex C (normative) Squeeze-off technique	32
Bibliography	33