

DIN EN 1555-4:2026-02 (E)

Plastics piping systems for the supply of gaseous fuels - Polyethylene (PE) - Part 4: Valves

Contents		Page
European foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	8
3.1	General	8
3.2	Terms relating to design	8
4	Symbols and abbreviations	9
5	Material	9
5.1	PE compound for valves	9
5.2	Material for non-polyethylene components	9
5.2.1	General	9
5.2.2	Metal parts	10
5.2.3	Sealing materials	10
5.2.4	Greases and lubricants	10
5.2.5	Assembly	10
6	General characteristics	10
6.1	Appearance of the valve	10
6.2	Colour	10
6.3	Design	10
6.3.1	General	10
6.3.2	Valve body	10
6.3.3	Valve ends	10
6.3.4	Operating device	11
6.3.5	Seals	11
7	Geometrical characteristics	11
7.1	General	11
7.2	Measurement of dimensions	11
7.3	Dimensions of spigot ends for valves	11
7.4	Dimensions of valves with electrofusion sockets	11
7.5	Dimensions of the operating device	11
8	Mechanical characteristics of assembled valves	11
8.1	General	11
8.2	Requirements	12
8.2.1	General	12
8.2.2	Air flow rate	18
9	Physical characteristics	19
9.1	Conditioning	19
9.2	Requirements	19
10	Performance requirements	19

11	Technical file	19
12	Marking	20
12.1	General	20
12.2	Minimum required marking	20
12.3	Additional marking	21
13	Delivery conditions	21
Annex A (normative) Determination of the leaktightness of seat(s) and packing		22
A.1	General	22
A.2	Test piece	22
A.3	Procedure	22
A.3.1	Conditioning	22
A.3.2	Internal leaktightness test (fully closed valve)	22
A.3.3	External leaktightness test (half open valve)	22
A.4	Test report	23
Annex B (normative) Test method for leaktightness and ease of operation after tensile loading		24
B.1	Apparatus	24
B.2	Test piece	24
B.3	Conditions	24
B.4	Procedure	24
B.5	Test report	25
Bibliography		26