DIN EN 13245-1:2026-02 (E)

Plastics - Unplasticized poly(vinyl chloride) (PVC-U) profiles for building applications - Part 1: Designation of PVC-U profiles

Contents

Page

European foreword 3

1 Scope 5

2 Normative references 5

3 Terms and definitions 6
3.2 Type of profile 7

4 Designation of PVC-U profiles 8

5 Codification system for Data block 3 to Data block 5 8
5.1 Vicat softening temperature (Data block 3) 8
5.2 Modulus of elasticity in flexure (Data block 3) 9
5.3 Nominal linear mass (Data block 4) 9
5.4 Heat reversion at 100 °C (Data block 4) 10
5.5 Impact resistance (Data block 4) 10
5.6 Durability (Data block 5) 10
5.6.1 General 10
5.6.2 Test methods for ageing 11
5.6.3 Methods for assessing of ageing 12
5.6.4 Codification for properties after ageing 12

6 Required characteristics for Type 3, Type 4 and Type 5 profiles 14

7 Optional characteristics 15
7.1 Resistance to staining 15
7.2 Application and appearance of the surface finishing (only for Type 3, Type 4 and Type 5 profiles) 15
7.2.1 General 15
7.2.2 Single colour profiles 15
7.2.3 Non-uniform colour and texture profiles 15
7.2.4 Gloss 15

8 Example of the designation of a PVC-U profile 16

9 Use of rPVC-U or IRM 16

10 Design for recycling 16

Annex A (normative) Determination of the linear mass 17

Annex B (normative) Determination of the impact resistance 18

Annex C (normative) Determination of peel strength using a constant-load tensile test 21

Bibliography 24