

DIN EN 12608-1:2026-10 (E)

Unplasticized poly(vinyl chloride) (PVC-U) profiles for the fabrication of windows and doors - Classification, requirements and test methods - Part 1: Non-covered PVC-U profiles

Contents	Page
European foreword	4
1 Scope	6
2 Normative references	6
3 Terms and definitions	7
4 Classifications	10
4.1 General	10
4.2 Classification of climatic zones	10
4.3 Classification of material to the resistance to artificial weathering	11
4.4 Classification of main profiles according to the wall thickness of the external walls	11
5 Requirements	12
5.1 Material	12
5.2 Appearance	13
5.3 Dimensions and tolerances	13
5.3.1 General	13
5.3.2 Nominal shape	13
5.3.3 Wall thickness of main profiles	14
5.3.4 Tolerances on other dimensions	14
5.3.5 Deviation from straightness of the main profiles	14
5.4 Linear weight of the main profiles	14
5.5 Heat reversion	14
5.5.1 Main profiles	14
5.5.2 Auxiliary profiles	14
5.6 Behaviour after heating at 150 °C	14
5.7 Weldability	14
5.7.1 General	14
5.7.2 Tensile bending test	14
5.7.3 Compression bending test	15
5.8 Optional properties	15
6 Test methods	15
6.1 Visual inspection	15
6.2 Determination of dimensions	15
6.2.1 Measuring devices	15
6.2.2 Test specimen	15
6.2.3 Conditioning	15
6.2.4 Procedure	15
6.3 Determination of the linear weight of the profile	16
6.3.1 General	16
6.3.2 Using a balance	16
6.4 Determination of the thickness of a co-extruded layer	17
6.5 Determination of colorimetric coordinates	17
6.6 Determination of the ash content	17
6.7 Determination of the resistance of main profiles to impact by falling mass	17

7	Traceability	18
	Annex A (normative) Requirements for materials	19
A.1	General	19
A.2	Preparation of test specimens	22
A.2.1	General	22
A.2.2	Preparation of pressed plates	22
A.2.3	Material properties	22
	Annex B (normative) Calculation method for the determination of the radiant exposure and exposure time to be used for artificial weathering	23
B.1	General	23
B.2	Calculation	23
	Bibliography	26