

# ISO 4674-1:2003-09 (E)

## Rubber- or plastics-coated fabrics - Determination of tear resistance - Part 1: Constant rate of tear methods

---

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Apparatus .....</b>	<b>2</b>
<b>5</b>	<b>Atmospheres for conditioning and testing .....</b>	<b>2</b>
<b>6</b>	<b>Method A -- Tongued (double-tear) test piece .....</b>	<b>2</b>
<b>7</b>	<b>Method B -- Trouser-shaped (single-tear) test piece .....</b>	<b>6</b>
<b>8</b>	<b>Precision .....</b>	<b>7</b>
<b>9</b>	<b>Test report .....</b>	<b>7</b>
<b>Annexes Annex A (informative) Example of calculation of tear force .....</b>		<b>8</b>
<b>A.1</b>	<b>Example of tear trace .....</b>	<b>8</b>
<b>A.2</b>	<b>Alternative approach using medium-sized peaks .....</b>	<b>9</b>
<b>Annex B (informative) Wide-width trouser-shaped test piece .....</b>		<b>10</b>