

# ISO 13894-2 :2005-07 (E)

High-pressure decorative laminates\_ - Composite elements\_ - Part\_2: Specifications for composite elements with wood-based substrates for interior use

---

## Contents

Page

Foreword.....	iv
<b>1</b> <b>Scope</b> .....	<b>1</b>
<b>2</b> <b>Normative references</b> .....	<b>1</b>
<b>3</b> <b>Terms and definitions</b> .....	<b>1</b>
<b>4</b> <b>Requirements</b> .....	<b>2</b>
<b>5</b> <b>Properties</b> .....	<b>2</b>
5.1 <b>Appearance</b> .....	<b>2</b>
5.2 <b>Dimensional tolerances</b> .....	<b>3</b>
5.3 <b>Surface bond strength</b> .....	<b>6</b>
5.4 <b>Perpendicular tensile strength</b> .....	<b>6</b>
5.5 <b>Glue-line quality</b> .....	<b>6</b>
5.6 <b>Substrate protection against water vapour (thickness swell)</b> .....	<b>6</b>
5.7 <b>Surface impact resistance</b> .....	<b>6</b>
<b>Annex A</b> (informative) <b>Optional properties</b> .....	<b>7</b>
A.1 <b>General</b> .....	<b>7</b>
A.2 <b>Resistance to axial withdrawal of wood screws (screw-holding)</b> .....	<b>7</b>
A.3 <b>Resistance to elevated temperature (short-term exposure)</b> .....	<b>7</b>
A.4 <b>Resistance to elevated temperature (long-term exposure)</b> .....	<b>7</b>
A.5 <b>Resistance to water vapour</b> .....	<b>8</b>
A.6 <b>Flexural strength/flexural modulus of elasticity</b> .....	<b>8</b>
A.7 <b>Continuous-load capability</b> .....	<b>9</b>
A.8 <b>Water resistance (edge swell)</b> .....	<b>9</b>
<b>Annex B</b> (informative) <b>Reaction to fire</b> .....	<b>10</b>
<b>Annex C</b> (informative) <b>Formaldehyde emission</b> .....	<b>11</b>