DIN EN ISO 12086-2:2006-05 (E)

Plastics - Fluoropolymer dispersions and moulding and extrusion materials - Part 2: Preparation of test specimens and determination of properties (ISO 12086-2:2006)

Contents

Page

Foreword 2

1 Scope 4

2 Normative references 4

3 Terms and definitions 6

4 Abbreviated terms and symbols 7

5 Sampling 8

6 Preparation of test specimens 8

7 Conditioning and test conditions 8

8 General testing of fluoropolymers 8
8.1 Electrical properties 9
8.2 Mechanical properties 11
8.3 Thermal-transition temperatures 13
8.4 Density 14
8.5 Flammability by oxygen index 14
8.6 Particle size and size distribution 14

9 Testing of fluoropolymer dispersions 20
9.1 General 20
9.2 Preparation of test samples 21
9.3 Isolation of PTFE from dispersion 21
9.4 Coagulum in dispersions 22
9.5 Percentage polymer and surfactant in aqueous dispersion 22
9.6 PTFE solids content by hydrometer 23
9.7 pH of dispersions 24

10 Testing of PTFE and closely related materials 24
10.1 General 24
10.2 Preparation of test specimens by moulding 24
10.3 Bulk density 26
10.4 Extrusion pressure 30
10.5 Powder-flow time 35
10.6 Standard specific gravity (SSG), extended specific gravity (ESG) and thermal-instability index (TII) 37
10.7 Stretching-void index (SVI) 40

11 Testing of conventionally melt-processible fluoropolymers 41
11.1 Preparation of test specimens by moulding 41
11.2 Melt mass-flow rate (MFR) and melt volume-flow rate (MVR) 42

12 Other test methods used with fluoropolymers 44
12.1 Brittleness temperature of plastics and elastomers by impact 44
12.2 Coefficients of static and kinetic friction 44
12.3 Zero-strength time 44

Annex A (informative) Listing of test methods (alphabetical order) 45

Annex B (informative) Designatory properties for common fluoropolymer types with cross-reference listing to the tables for codes in ISO 12086-1 and the test methods in ISO 12086-2 46

Bibliography 48