

# ISO 6993-1:2006-06 (E)

## Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels - Part 1: Pipes for a maximum operating pressure of 1 bar (100 kPa)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
1	<b>Scope .....</b>	<b>1</b>
2	<b>Normative references .....</b>	<b>1</b>
3	<b>Terms and definitions .....</b>	<b>2</b>
4	<b>Symbols and abbreviated terms .....</b>	<b>4</b>
5	<b>Material .....</b>	<b>5</b>
6	<b>General characteristics .....</b>	<b>6</b>
7	<b>Geometrical characteristics .....</b>	<b>6</b>
8	<b>Physical characteristics .....</b>	<b>8</b>
9	<b>Mechanical characteristics .....</b>	<b>8</b>
10	<b>General requirements for pipes .....</b>	<b>9</b>
11	<b>Test methods .....</b>	<b>10</b>
12	<b>Marking .....</b>	<b>11</b>
<b>Annex A (normative) Determination of resistance to gas constituents .....</b>		<b>12</b>
<b>Annex B (normative) Determination of resistance of pipes to external blows .....</b>		<b>16</b>
<b>Bibliography .....</b>		<b>17</b>