ISO 6993-3:2006-06 (E)

Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the su pply of gaseous fuels - Part 3: Fittings and saddles for a maximum operating pressure of 1 bar (100 kPa)

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms, definitions, symbols and abbreviated terms 2

4 Material 5

5 General characteristics of fittings/saddles 6

6 Geometrical characteristics 6

7 Physical characteristics 7

8 Mechanical characteristics 8

9 Saddle design and construction 9

10 Performance requirements 10

11 Test methods 11

12 Marking 11

Annex A (normative) Determination of resistance to external blows at 0 °C for fittings 13

Annex B (normative) Determination of resistance to external blows at 0 °C for saddles 15

Annex C (normative) Determination of tensile resistance of in-line fitting assemblies 18

Annex D (normative) Determination of leaktightness of saddle joints by internal air pressure, with and without mechanical loading 19

Annex E (normative) Determination of leaktightness of saddle joints under negative pressure and mechanical loading 21

Annex F (normative) Determination of leaktightness under constant load and by tensile testing at constant speed of lateral connections (end-load resistant joints of tapping saddles with PE service pipe lines) 23

Bibliography 25