

ISO 6993-3:2006-06 (E)

Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels - Part 3: Fittings and saddles for a maximum operating pressure of 1 bar (100 kPa)

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms, definitions, symbols and abbreviated terms	2
4	Material	5
5	General characteristics of fittings/saddles	6
6	Geometrical characteristics	6
7	Physical characteristics	7
8	Mechanical characteristics	8
9	Saddle design and construction	9
10	Performance requirements	10
11	Test methods	11
12	Marking	11
Annex A (normative)	Determination of resistance to external blows at 0 °C for fittings	13
Annex B (normative)	Determination of resistance to external blows at 0 °C for saddles	15
Annex C (normative)	Determination of tensile resistance of in-line fitting assemblies	18
Annex D (normative)	Determination of leaktightness of saddle joints by internal air pressure, with and without mechanical loading	19
Annex E (normative)	Determination of leaktightness of saddle joints under negative pressure and mechanical loading	21
Annex F (normative)	Determination of leaktightness under constant load and by tensile testing at constant speed of lateral connections (end-load resistant joints of tapping saddles with PE service pipe lines)	23
Bibliography		25