

# ISO 6993-3:2006-06 (E)

Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels - Part 3: Fittings and saddles for a maximum operating pressure of 1 bar (100 kPa)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
1	Scope .....	1
2	Normative references .....	1
3	Terms, definitions, symbols and abbreviated terms .....	2
4	Material .....	5
5	General characteristics of fittings/saddles .....	6
6	Geometrical characteristics .....	6
7	Physical characteristics .....	7
8	Mechanical characteristics .....	8
9	Saddle design and construction .....	9
10	Performance requirements .....	10
11	Test methods .....	11
12	Marking .....	11
Annex A (normative)	Determination of resistance to external blows at 0 °C for fittings .....	13
Annex B (normative)	Determination of resistance to external blows at 0 °C for saddles .....	15
Annex C (normative)	Determination of tensile resistance of in-line fitting assemblies .....	18
Annex D (normative)	Determination of leaktightness of saddle joints by internal air pressure, with and without mechanical loading .....	19
Annex E (normative)	Determination of leaktightness of saddle joints under negative pressure and mechanical loading .....	21
Annex F (normative)	Determination of leaktightness under constant load and by tensile testing at constant speed of lateral connections (end-load resistant joints of tapping saddles with PE service pipe lines) .....	23
Bibliography .....		25