

# ISO 6993-3:2006-06 (E)

Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels - Part 3: Fittings and saddles for a maximum operating pressure of 1 bar (100 kPa)

---

<b>Contents</b>	<b>Page</b>
Foreword .....	iv
1 Scope .....	1
2 Normative references .....	1
3 Terms, definitions, symbols and abbreviated terms .....	2
4 Material .....	5
5 General characteristics of fittings/saddles .....	6
6 Geometrical characteristics .....	6
7 Physical characteristics .....	7
8 Mechanical characteristics .....	8
9 Saddle design and construction .....	9
10 Performance requirements .....	10
11 Test methods .....	11
12 Marking .....	11
Annex A (normative) Determination of resistance to external blows at 0 °C for fittings .....	13
Annex B (normative) Determination of resistance to external blows at 0 °C for saddles .....	15
Annex C (normative) Determination of tensile resistance of in-line fitting assemblies .....	18
Annex D (normative) Determination of leaktightness of saddle joints by internal air pressure, with and without mechanical loading .....	19
Annex E (normative) Determination of leaktightness of saddle joints under negative pressure and mechanical loading .....	21
Annex F (normative) Determination of leaktightness under constant load and by tensile testing at constant speed of lateral connections (end-load resistant joints of tapping saddles with PE service pipe lines) .....	23
Bibliography .....	25