

# ISO 22088-2:2006-08 (E)

## Plastics - Determination of resistance to environmental stress cracking (ESC) - Part 2: Constant tensile load method

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Principle .....</b>	<b>2</b>
<b>4</b>	<b>Apparatus .....</b>	<b>2</b>
<b>5</b>	<b>Conditioning and test conditions .....</b>	<b>3</b>
<b>5.1</b>	<b>Conditioning .....</b>	<b>3</b>
<b>5.2</b>	<b>Test temperature .....</b>	<b>3</b>
<b>5.3</b>	<b>Test medium .....</b>	<b>3</b>
<b>6</b>	<b>Test stress .....</b>	<b>4</b>
<b>6.1</b>	<b>Maximum permissible stress .....</b>	<b>4</b>
<b>6.2</b>	<b>Method A .....</b>	<b>4</b>
<b>6.3</b>	<b>Method B .....</b>	<b>4</b>
<b>6.4</b>	<b>Method C .....</b>	<b>4</b>
<b>7</b>	<b>Test specimens .....</b>	<b>4</b>
<b>7.1</b>	<b>General .....</b>	<b>4</b>
<b>7.2</b>	<b>Shape and dimensions .....</b>	<b>4</b>
<b>7.3</b>	<b>Number .....</b>	<b>5</b>
<b>7.4</b>	<b>Preparation .....</b>	<b>5</b>
<b>8</b>	<b>Procedure .....</b>	<b>6</b>
<b>9</b>	<b>Expression of results .....</b>	<b>7</b>
<b>9.1</b>	<b>Method A .....</b>	<b>7</b>
<b>9.2</b>	<b>Method B .....</b>	<b>7</b>
<b>9.3</b>	<b>Method C .....</b>	<b>7</b>
<b>10</b>	<b>Precision .....</b>	<b>7</b>
<b>11</b>	<b>Test report .....</b>	<b>8</b>
<b>Annex A (informative) Examples of stresses to be applied .....</b>		<b>9</b>
<b>Bibliography .....</b>		<b>10</b>