

ISO 22088-2:2006-08 (E)

Plastics - Determination of resistance to environmental stress cracking (ESC) - Part 2: Constant tensile load method

| Contents | Page |
|---|-----------|
| Foreword | iv |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Principle | 2 |
| 4 Apparatus | 2 |
| 5 Conditioning and test conditions | 3 |
| 5.1 Conditioning | 3 |
| 5.2 Test temperature | 3 |
| 5.3 Test medium | 3 |
| 6 Test stress | 4 |
| 6.1 Maximum permissible stress | 4 |
| 6.2 Method A | 4 |
| 6.3 Method B | 4 |
| 6.4 Method C | 4 |
| 7 Test specimens | 4 |
| 7.1 General | 4 |
| 7.2 Shape and dimensions | 4 |
| 7.3 Number | 5 |
| 7.4 Preparation | 5 |
| 8 Procedure | 6 |
| 9 Expression of results | 7 |
| 9.1 Method A | 7 |
| 9.2 Method B | 7 |
| 9.3 Method C | 7 |
| 10 Precision | 7 |
| 11 Test report | 8 |
| Annex A (informative) Examples of stresses to be applied | 9 |
| Bibliography | 10 |