

# ISO 17484-1:2006-10 (E)

## Plastics piping systems - Multilayer pipe systems for indoor gas installations with a maximum operating pressure up to and including 5 bar (500 kPa) - Part 1: Specifications for systems

---

| <b>Contents</b>   |  | <b>Page</b> |
|---|--|-------------|
| Foreword .....  |  | v           |
| Introduction .....  |  | vi          |
| <b>1</b>  | <b>Scope .....</b>   | <b>1</b>    |
| <b>2</b>  | <b>Normative references .....</b>  | <b>2</b>    |
| <b>3</b>  | <b>Terms, definitions and symbols .....</b>  | <b>3</b>    |
| <b>3.1</b>  | <b>Structural definitions .....</b>  | <b>3</b>    |
| <b>3.2</b>  | <b>Geometrical definitions .....</b>   | <b>3</b>    |
| <b>3.3</b>  | <b>Definitions related to pressure .....</b>   | <b>4</b>    |
| <b>3.4</b>  | <b>Materials definitions .....</b>   | <b>4</b>    |
| <b>3.5</b>  | <b>Definitions related to material characteristics .....</b>                             | <b>5</b>    |
| <b>3.6</b>  | <b>Terms related to service conditions .....</b>   | <b>5</b>    |
| <b>4</b>  | <b>Requirements for the system .....</b>   | <b>6</b>    |
| <b>4.1</b>  | <b>Pressure drop .....</b>   | <b>6</b>    |
| <b>4.2</b>  | <b>Bending .....</b>   | <b>6</b>    |
| <b>4.3</b>  | <b>Corrosive conditions .....</b>  | <b>6</b>    |
| <b>5</b>  | <b>Pipes .....</b>   | <b>6</b>    |
| <b>5.1</b>  | <b>Material .....</b>  | <b>6</b>    |
| <b>5.2</b>  | <b>General characteristics .....</b>   | <b>7</b>    |
| <b>5.3</b>  | <b>Dimensions of pipes .....</b>   | <b>7</b>    |
| <b>5.4</b>  | <b>Mechanical properties .....</b>   | <b>8</b>    |
| <b>5.5</b>  | <b>Physical properties .....</b>   | <b>9</b>    |
| <b>6</b>  | <b>Fittings .....</b>  | <b>10</b>   |
| <b>6.1</b>  | <b>General .....</b>   | <b>10</b>   |
| <b>6.2</b>  | <b>Materials .....</b>   | <b>11</b>   |
| <b>6.3</b>  | <b>Dimensions .....</b>  | <b>11</b>   |
| <b>6.4</b>  | <b>Transition fittings .....</b>   | <b>11</b>   |
| <b>6.5</b>  | <b>Rubber rings .....</b>  | <b>11</b>   |
| <b>7</b>  | <b>Fitness for purpose .....</b>   | <b>11</b>   |
| <b>7.1</b>  | <b>Diameter classes .....</b>  | <b>11</b>   |
| <b>7.2</b>  | <b>Relation between maximum operating pressure and qualification test pressure .....</b> | <b>11</b>   |
| <b>7.3</b>  | <b>Requirements .....</b>  | <b>12</b>   |
| <b>8</b>  | <b>Marking and documentation .....</b>   | <b>13</b>   |
| <b>8.1</b>  | <b>Legibility .....</b>  | <b>13</b>   |
| <b>8.2</b>  | <b>Damage .....</b>  | <b>13</b>   |
| <b>8.3</b>  | <b>Minimum marking requirements .....</b>  | <b>13</b>   |
| <b>Annex A (normative) List of the reference product standards .....</b>              |  | <b>15</b>   |
| <b>Annex B (normative) Test for delamination and strength of the joint line .....</b> |  | <b>16</b>   |

|   |           |
|---|-----------|
| <b>Annex C (normative) Resistance to gas constituents .....</b>                   | <b>18</b> |
| <b>Annex D (normative) Thermal durability of the outer layer of M-pipes .....</b> | <b>19</b> |
| <b>Annex E (normative) Adhesion test .....</b>                                    | <b>21</b> |
| <b>Annex F (normative) Odour permeability .....</b>                               | <b>22</b> |
| <b>Annex G (normative) Resistance to tensile load on joints .....</b>             | <b>23</b> |
| <b>Annex H (normative) Crush test on joints .....</b>                             | <b>25</b> |
| <b>Annex I (normative) Impact resistance test on joints .....</b>                 | <b>27</b> |
| <b>Annex J (normative) Thermal cycling test on joints .....</b>                   | <b>29</b> |
| <b>Annex K (normative) Repeated bending test .....</b>                            | <b>31</b> |
| <b>Bibliography .....</b>   | <b>33</b> |