

DIN EN ISO 307:2007-08 (E)

Plastics - Polyamides - Determination of viscosity number (ISO 307:2007)

Contents		Page
Foreword		3
Introduction		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	6
4	Principle	7
5	Reagents and materials	7
5.1	Solvents and reagents	7
5.2	Cleaning liquids	8
6	Apparatus	8
7	Preparation of test samples	9
7.1	General	9
7.2	Samples containing less than 98 % (by mass) polyamide	9
8	Calculation of test portion	10
9	Selection of solvent	10
10	Procedure	11
10.1	Cleaning of the viscometer	11
10.2	Preparation of test solution	11
10.3	Measurement of flow times	13
11	Expression of results	14
12	Repeatability and reproducibility	14
13	Relationship between the viscosity number determined in 96 % (by mass) sulfuric acid solution and the viscosity determined in various solvents	15
14	Test report	15
Annex A (informative) Determination of the concentration of commercial sulfuric acid (95 % to 98 %) and adjustment to 96 % by titration		17
Annex B (informative) Determination of the concentration of sulfuric acid (95 % to 98 %) and adjustment to 96 % by flow time measurement in a small capillary viscometer		20
Annex C (informative) Determination of the concentration of commercial formic acid and adjustment to 90 % by titration		22
Annex D (informative) Determination of the concentration of commercial formic acid and adjustment to 90 % by density measurement		24

Annex E (informative) Relationship between the viscosity number determined in 96 % (by mass) sulfuric acid solution and the viscosity determined in various solvents	27
Bibliography	37