

ISO 21367:2007-05 (E)

Plastics - Reaction to fire - Test method for flame spread and combustion product release from vertically oriented specimens

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Symbols	3
5	General principles	3
6	Test apparatus	4
7	Test specimen	13
7.1	Surface characteristics	13
7.2	Exposed surface	13
7.3	Number and size of specimen	13
7.4	Construction of specimen	14
7.5	Conditioning of specimens	14
7.6	Preparation	14
8	Test environment	16
9	Calibration	16
9.1	Preliminary calibration	16
9.2	Operating calibrations	17
9.3	Less frequent calibrations	18
10	Test procedure	19
10.1	Warning	19
10.2	Initial preparation	19
10.3	Procedure	20
11	Calculation	21
11.1	Calibration constant for oxygen consumption analysis	21
11.2	Heat release rate	21
11.3	Exhaust duct flow rate	22
11.4	Smoke production rate (SPR)	22
12	Test report	23
Annex A (normative) Additional calculations		24
Annex B (informative) Simplified version of the apparatus		26
Annex C (informative) Repeatability of the test method		28
Annex D (informative) Calibration of the working heat flux meter		32
Bibliography		33