DIN EN 12102:2008-09 (E)

Air conditioners, liquid chilling packages, heat pumps and d ehumidifiers with electrically driven compressors for space heating and cooling - Measurement of airborne noise - Determination of the sound power level

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 6

3 Definitions and symbols 7
3.1 General 7
3.2 Symbols 7
3.2.1 Non ducted units 7
3.2.2 Ducted units 7
3.3 Standard operating conditions 7

4 Measuring instruments 8

5 Operation of the unit 9

6 Installation 11
6.1 General points 11
6.2 Ducted units 11
6.2.1 Installation 11
6.2.2 Duct end correction 11
6.2.3 Bend correction 12
6.2.4 Pressure and airflow measurements 13
6.2.5 Casing radiated test 14
6.3 Wall mounted 14
6.4 Ceiling Mounted 14
6.5 Window-type 14
6.6 Multisplits 14
6.7 Single ducts 14
6.7.1 Casing radiated test: 14
6.7.2 Ducted outlet 15

7 Acoustic measurement methods 15
7.1 Frequency range 15
7.2 To choose a method 15
7.2.1 General 15
7.2.2 Available test facilities 15
7.2.3 Target of measurement 16
7.3 Reverberation room methods 16
7.3.1 General 16
7.3.2 Non ducted units 16
7.3.3 Ducted units 17
7.4 Installation of the free field over a reflecting plane method 17
7.4.1 General 17
7.4.2 Reference surface 17
7.4.3 Measuring surface 18

8 Uncertainty of measurement results 20

9 Test report 20
9.1 General 20
9.2 Unit specification 20
9.3 Operating conditions, installation and environmental conditions 20
9.4 Measurement instruments 20
9.5 Measured values and results 21

Annex A (normative) Energy labelling application 22

A.1 General 22
A.2 Test procedure 22
A.3 Tolerances permitted on declared values 22

Annex B (normative) Specific measurement for variable capacity units 23

B.1 General requirements 23
B.2 Test mode 23
B.3 Measurements process 23

Bibliography 24