

# DIN EN 14624:2012-04 (E)

## Performance of portable leak detectors and of room monitors for halogenated refrigerants

---

<b>Contents</b>		<b>Page</b>
Foreword .....		4
1	Scope .....	5
2	Normative references .....	5
3	Terms and definitions .....	5
4	Symbols and abbreviations .....	7
5	Types of portable leak detectors and room monitors .....	7
6	General requirements for all portable leak detectors and room monitors .....	7
6.1	Gas type .....	7
6.2	Capabilities .....	7
6.3	Output signal .....	8
6.4	Response time .....	8
6.5	Recovery time (clean up time) .....	8
6.6	Repeatability .....	8
6.7	Calibration .....	8
7	Specific requirements for locating portable leak detectors .....	8
7.1	General .....	8
7.2	Lowest detectable leakage rate threshold when the leak detector is stationary .....	9
7.3	Lowest detectable leakage rate threshold value when the detector probe is moving .....	9
7.4	Leak detection in a contaminated environment .....	9
8	Specific requirements for room monitors .....	10
8.1	General .....	10
8.2	Lowest detectable concentration (lower detection limit) .....	10
8.3	Highest tolerable concentration (upper detection limit) .....	10
8.4	Upper and lower alarm thresholds .....	10
8.5	Response time for alarm trigger .....	10
9	Calibration leaks .....	10
9.1	General .....	10
9.2	Calibration gases .....	10
10	Test apparatus .....	11
10.1	General .....	11
10.2	Apparatus no. 1: detector probe stationary at the orifice of a calibration leak .....	11
10.3	Apparatus no. 2: detector probe moved with defined speed and distance in front of a calibration leak .....	11
10.4	Apparatus no. 3: Chamber with monitored concentration .....	12
11	Performance tests .....	12
11.1	Performance test of locating leak detector .....	12
11.1.1	Test no. 1: Static detection .....	12
11.1.2	Test no. 2: dynamic detection limit .....	13
11.1.3	Test no. 3: detection limit in contaminated environment .....	13
11.1.4	Test no. 4: recovery time .....	13

<b>11.2</b>	<b>Performance tests of room monitor .....</b>	<b>13</b>
<b>11.2.1</b>	<b>General .....</b>	<b>13</b>
<b>11.2.2</b>	<b>Test a) to determine the upper and lower detection limits .....</b>	<b>13</b>
<b>11.2.3</b>	<b>Test b) to determine response time .....</b>	<b>14</b>
<b>11.2.4</b>	<b>Test c) to determine recovery time from exposure to a large concentration .....</b>	<b>14</b>
<b>12</b>	<b>Instrument characteristics and reporting of test results .....</b>	<b>15</b>
<b>12.1</b>	<b>Characteristics of locating leak detector .....</b>	<b>15</b>
<b>12.2</b>	<b>Characteristics of room monitors .....</b>	<b>15</b>
<b>13</b>	<b>Technical data .....</b>	<b>16</b>
<b>13.1</b>	<b>Locating leak detectors .....</b>	<b>16</b>
<b>13.2</b>	<b>Measuring leak detectors .....</b>	<b>16</b>
<b>13.3</b>	<b>All portable leak detectors .....</b>	<b>16</b>
<b>13.4</b>	<b>Room monitor .....</b>	<b>16</b>
<b>Annex A (informative) Conversion factors of leakage rate units .....</b>		<b>18</b>
<b>Annex B (informative) Correlation between test gas concentration and leakage rate .....</b>		<b>19</b>
<b>Annex C (informative) Guidelines for monitoring a machinery room or space for gas leaks .....</b>		<b>23</b>