

# DIN EN 14825:2019-07 (E)

Air conditioners, liquid chilling packages and heat pumps, with electrically driven compressors, for space heating and cooling - Testing and rating at part load conditions and calculation of seasonal performance

---

| <b>Contents</b>         |  | <b>Page</b> |
|-------------------------|--|-------------|
| European foreword ..... |  | 7           |
| Introduction .....      |  | 9           |
| <b>1</b>                | <b>Scope .....</b>   | <b>10</b>   |
| <b>2</b>                | <b>Normative references .....</b>  | <b>10</b>   |
| <b>3</b>                | <b>Terms, definitions, symbols, abbreviated terms and units .....</b>                                    | <b>11</b>   |
| <b>3.1</b>              | <b>Terms and definitions .....</b>   | <b>11</b>   |
| <b>3.2</b>              | <b>Symbols, abbreviated terms and units .....</b>  | <b>23</b>   |
| <b>4</b>                | <b>Part load conditions for space cooling .....</b>  | <b>28</b>   |
| <b>4.1</b>              | <b>General .....</b>   | <b>28</b>   |
| <b>4.2</b>              | <b>Air-to-air units .....</b>  | <b>28</b>   |
| <b>4.3</b>              | <b>Water(brine)-to-air units .....</b>   | <b>28</b>   |
| <b>4.4</b>              | <b>Air-to-water(brine) units .....</b>   | <b>29</b>   |
| <b>4.5</b>              | <b>Water(brine)-to-water(brine) units .....</b>  | <b>29</b>   |
| <b>5</b>                | <b>Calculation methods for seasonal space cooling efficiency s,c, SEER and SEERon .....</b>              | <b>30</b>   |
| <b>5.1</b>              | <b>General .....</b>   | <b>30</b>   |
| <b>5.2</b>              | <b>Calculation of the seasonal space cooling efficiency s,c .....</b>                                    | <b>31</b>   |
| <b>5.3</b>              | <b>General formula for calculation of SEER .....</b>   | <b>31</b>   |
| <b>5.4</b>              | <b>Calculation of the reference annual cooling demand QC .....</b>                                       | <b>31</b>   |
| <b>5.5</b>              | <b>Calculation of the reference annual energy consumption for cooling QCE .....</b>                      | <b>32</b>   |
| <b>5.6</b>              | <b>Calculation of SEERon .....</b>   | <b>32</b>   |
| <b>5.7</b>              | <b>Calculation procedure for determination of EERbin values at part load conditions A, B, C, D .....</b> | <b>33</b>   |
| <b>5.7.1</b>            | <b>General .....</b>   | <b>33</b>   |
| <b>5.7.2</b>            | <b>Calculation procedure for fixed capacity units .....</b>  | <b>33</b>   |
| <b>5.7.3</b>            | <b>Calculation procedure for staged and variable capacity units .....</b>                                | <b>34</b>   |
| <b>6</b>                | <b>Part load conditions for space heating .....</b>  | <b>34</b>   |
| <b>6.1</b>              | <b>General .....</b>   | <b>34</b>   |
| <b>6.2</b>              | <b>Air-to-air units .....</b>  | <b>35</b>   |
| <b>6.3</b>              | <b>Water(brine)-to-air-units .....</b>   | <b>36</b>   |
| <b>6.4</b>              | <b>Air-to-water(brine) units .....</b>   | <b>37</b>   |
| <b>6.4.1</b>            | <b>General .....</b>   | <b>37</b>   |
| <b>6.4.2</b>            | <b>Low temperature application .....</b>   | <b>38</b>   |
| <b>6.4.3</b>            | <b>Intermediate temperature application .....</b>  | <b>39</b>   |
| <b>6.4.4</b>            | <b>Medium temperature application .....</b>  | <b>40</b>   |
| <b>6.4.5</b>            | <b>High temperature application .....</b>  | <b>41</b>   |
| <b>6.5</b>              | <b>DX-to-water(brine) and water(brine)-to-water(brine) units .....</b>                                   | <b>41</b>   |
| <b>6.5.1</b>            | <b>General .....</b>   | <b>41</b>   |
| <b>6.5.2</b>            | <b>Low temperature application .....</b>   | <b>42</b>   |
| <b>6.5.3</b>            | <b>Intermediate temperature application .....</b>  | <b>43</b>   |
| <b>6.5.4</b>            | <b>Medium temperature application .....</b>  | <b>44</b>   |
| <b>6.5.5</b>            | <b>High temperature application .....</b>  | <b>45</b>   |

|        |  |    |
|--------|--|----|
| 7      | Test methods for hybrid heat pumps .....   | 46 |
| 7.1    | General .....  | 46 |
| 7.2    | Separated test method .....  | 46 |
| 7.3    | Combined test method .....   | 46 |
| 7.3.1  | General .....  | 46 |
| 7.3.2  | Calculation of gas input .....   | 46 |
| 7.3.3  | Calculation of liquid fuel input .....   | 47 |
| 7.3.4  | Calculation of annual fossil fuel consumption .....  | 47 |
| 8      | Calculation methods for seasonal space heating efficiency s,h, SCOP, SCOPon and SCOPnet .....  | 47 |
| 8.1    | General .....  | 47 |
| 8.2    | Calculation of the seasonal space heating efficiency s,h .....   | 48 |
| 8.3    | General formula for calculation of SCOP .....  | 48 |
| 8.4    | Calculation of the reference annual heating demand QH .....  | 48 |
| 8.5    | Calculation of the annual energy consumption for heating QHE .....   | 49 |
| 8.6    | Calculation of SCOPon and SCOPnet .....  | 49 |
| 8.6.1  | Calculation for all systems except hybrid heat pumps .....   | 49 |
| 8.6.2  | Calculation for hybrid heat pumps .....  | 51 |
| 8.7    | Calculation procedure for determination of COPbin values at part load conditions A to G .....  | 54 |
| 8.7.1  | General .....  | 54 |
| 8.7.2  | Calculation procedure for fixed capacity units .....   | 54 |
| 8.7.3  | Calculation procedure for staged and variable capacity units .....   | 55 |
| 9      | Part load conditions for process cooling .....   | 55 |
| 10     | Calculation method for SEPR .....  | 57 |
| 10.1   | General formula for calculation of SEPR .....  | 57 |
| 10.2   | Calculation procedure for determination of EERbin values at part load conditions A, B, C, D .....                                      | 58 |
| 10.2.1 | General .....  | 58 |
| 10.2.2 | Calculation procedure for fixed capacity process chillers .....  | 58 |
| 10.2.3 | Calculation procedure for variable capacity process chillers .....   | 59 |
| 11     | Test methods for testing capacities, EERbin and COPbin values during active mode at part load conditions .....                         | 59 |
| 11.1   | General .....  | 59 |
| 11.2   | Refrigerant piping .....   | 59 |
| 11.3   | Basic principles .....   | 60 |
| 11.4   | Uncertainties of measurement .....   | 62 |
| 11.5   | Test procedures for units with fixed capacity .....  | 62 |
| 11.5.1 | General .....  | 62 |
| 11.5.2 | Air-to-air and water(brine)-to-air units - Determination of the degradation coefficient Cd .....                                       | 64 |
| 11.5.3 | Air-to-water(brine), water(brine)-to-water(brine) and DX-to-water(brine) units - Determination of the degradation coefficient Cd ..... | 65 |
| 11.6   | Test procedure for staged and variable capacity units .....  | 66 |
| 11.6.1 | General .....  | 66 |
| 11.6.2 | Settings for the required capacity ratio .....   | 66 |
| 11.6.3 | Compensation method .....  | 67 |
| 12     | Test methods for electric power input during thermostat-off mode, standby mode and crankcase heater mode and off mode .....            | 67 |
| 12.1   | Uncertainties of measurement .....   | 67 |
| 12.2   | Measurement of electric power input during thermostat-off mode .....   | 67 |
| 12.3   | Measurement of the electric power input during standby mode .....  | 68 |
| 12.4   | Measurement of the electric power input during crankcase heater mode .....   | 68 |
| 12.5   | Measurement of the electric power input during off mode .....  | 68 |
| 13     | Test report .....  | 68 |
| 14     | Technical documentation .....  | 69 |

|   |           |
|---|-----------|
| <b>Annex A (normative) Applicable climate bins and hours for air conditioners with rated capacity of 12 kW for cooling, or heating if the product has no cooling function</b> | <b>70</b> |
| <b>A.1 Climate bins</b>   | <b>70</b> |
| <b>A.1.1 Bin limit temperature</b>  | <b>70</b> |
| <b>A.1.2 Cooling</b>  | <b>70</b> |
| <b>A.1.3 Heating</b>  | <b>70</b> |
| <b>A.2 Hours for active mode, thermostat-off, standby, off mode</b>   | <b>72</b> |
| <b>A.2.1 Cooling</b>  | <b>72</b> |
| <b>A.2.2 Heating</b>  | <b>72</b> |
| <b>A.3 Hours used for crankcase heater mode</b>   | <b>73</b> |
| <b>A.3.1 Cooling</b>  | <b>73</b> |
| <b>A.3.2 Heating</b>  | <b>73</b> |
| <b>Annex B (normative) Applicable climate bins and hours for air/water(brine)/DX-to- water(brine) heat pumps with a rated heat output 400kW</b>                               | <b>74</b> |
| <b>B.1 Climate bins</b>   | <b>74</b> |
| <b>B.1.1 Bin limit temperature</b>  | <b>74</b> |
| <b>B.1.2 Heating</b>  | <b>74</b> |
| <b>B.2 Hours for active, thermostat-off, standby and off modes - Heating</b>  | <b>75</b> |
| <b>B.3 Hours used for crankcase heater mode - Heating</b>   | <b>76</b> |
| <b>Annex C (normative) Applicable climate bins and hours for process chillers</b>   | <b>77</b> |
| <b>C.1 Climate bins</b>   | <b>77</b> |
| <b>Annex D (normative) Applicable climate bins and hours for air-to-air units &gt; 12 kW, water(brine)-to-air units and comfort chillers</b>                                  | <b>79</b> |
| <b>D.1 Climate bins</b>   | <b>79</b> |
| <b>D.1.1 Bin limit temperature</b>  | <b>79</b> |
| <b>D.1.2 Cooling</b>  | <b>79</b> |
| <b>D.1.3 Heating</b>  | <b>80</b> |
| <b>D.2 Hours for active, thermostat-off, standby and off modes</b>  | <b>81</b> |
| <b>D.2.1 Cooling</b>  | <b>81</b> |
| <b>D.2.2 Heating</b>  | <b>82</b> |
| <b>D.3 Hours used for crankcase heater mode</b>   | <b>82</b> |
| <b>D.3.1 Cooling</b>  | <b>82</b> |
| <b>D.3.2 Heating</b>  | <b>82</b> |
| <b>Annex E (normative) Templates for technical documentation</b>  | <b>83</b> |
| <b>E.1 General</b>  | <b>83</b> |
| <b>E.2 Air-to-air units 12 kW</b>   | <b>83</b> |
| <b>E.3 Space heaters: air-to-water(brine), water(brine)-to-water(brine) and DX-to- water(brine) units 400kW</b>   | <b>86</b> |
| <b>E.4 Hybrid heat pumps</b>  | <b>89</b> |
| <b>E.5 Process Chillers</b>   | <b>91</b> |
| <b>E.6 Comfort chillers, air-to-air (&gt;12 kW) and water(brine)-to-air air conditioners not exceeding 2 MW</b>   | <b>92</b> |
| <b>E.7 Air-to-air and water(brine)-to-air heat pumps not exceeding 1 MW</b>   | <b>93</b> |
| <b>Annex F (informative) Determination of water(brine) temperature for fixed capacity units with variable outlet temperature</b>  | <b>95</b> |
| <b>F.1 General</b>  | <b>95</b> |
| <b>F.2 Test procedure for an air-to-water unit with fixed water flow rate</b>   | <b>95</b> |
| <b>F.3 Test procedure for an air-to-water unit with variable water flow rate</b>  | <b>97</b> |
| <b>Annex G (informative) Calculation example for SEERon and SEER - Application to a reversible air-to-air unit with variable capacity</b>                                     | <b>99</b> |

|   |   |            |
|---|---|------------|
| <b>G.1</b>  | <b>Calculation of SEERon .....</b>  | <b>99</b>  |
| <b>G.2</b>  | <b>Calculation of SEER .....</b>  | <b>101</b> |
| <b>G.2.1</b>  | <b>Calculation of reference annual cooling demand (QC) according to Formula (3) .....</b>                                     | <b>101</b> |
| <b>G.2.2</b>  | <b>Calculation of SEER according to Formula (6) .....</b>   | <b>101</b> |
| <b>Annex H (informative) Calculation example for SCOPon and SCOPnet - Application to a fixed capacity air-to-water(brine) heat pump used for low temperature application .....</b>            |   | <b>102</b> |
| <b>Annex I void .....</b>   |   | <b>107</b> |
| <b>Annex J (informative) Calculation example for SCOPon and SCOPnet - Application to a fixed capacity brine-to-water(brine) heat pump used for medium temperature application .....</b>       |   | <b>108</b> |
| <b>Annex K (informative) Calculation examples for SCOPon for hybrid heat pumps .....</b>  |   | <b>115</b> |
| <b>K.1</b>  | <b>Calculation example for SCOPon for variable speed hybrid heat pump based on heat pump and boiler separated tests .....</b> | <b>115</b> |
| <b>K.2</b>  | <b>Calculation example for SCOPon for hybrid heat pump using combined test method .....</b>                                   | <b>117</b> |
| <b>Annex L (informative) Calculation example for SEPR - Application to a process chiller with staged capacity .....</b>   |   | <b>119</b> |
| <b>L.1</b>  | <b>Rating performance .....</b>   | <b>119</b> |
| <b>Annex M (informative) Compensation methods for air-to-water(brine) and water(brine)- to-water(brine) units .....</b>   |   | <b>122</b> |
| <b>M.1</b>  | <b>General .....</b>  | <b>122</b> |
| <b>M.2</b>  | <b>Compensation system for reduced capacity test in cooling mode .....</b>  | <b>122</b> |
| <b>M.3</b>  | <b>Compensation system for reduced capacity test in heating mode .....</b>  | <b>122</b> |
| <b>Annex N (normative) Rating of outdoor units of multi-split air conditioners and heat pumps .....</b>   |   | <b>124</b> |
| <b>N.1</b>  | <b>General .....</b>  | <b>124</b> |
| <b>N.2</b>  | <b>Terms and definitions .....</b>  | <b>124</b> |
| <b>N.3</b>  | <b>Rating of outdoor units .....</b>  | <b>124</b> |
| <b>N.3.1</b>  | <b>General .....</b>  | <b>124</b> |
| <b>N.3.2</b>  | <b>Test procedure .....</b>   | <b>125</b> |
| <b>N.4</b>  | <b>Calculation of the SEER based on the EER<sub>outdoor</sub> .....</b>   | <b>125</b> |
| <b>N.5</b>  | <b>Calculation of the SCOP based on the COP<sub>outdoor</sub> .....</b>   | <b>125</b> |
| <b>Annex ZA (informative) Relationship between this European Standard and the ecodesign requirements of Commission Regulation (EU) No 206/2012 aimed to be covered .....</b>                  |   | <b>126</b> |
| <b>Annex ZB (informative) Relationship between this European Standard and the ecodesign requirements of Commission Regulation (EU) No 813/2013 aimed to be covered .....</b>                  |   | <b>128</b> |
| <b>Annex ZC (informative) Relationship between this European Standard and the energy labelling requirements of Commission Delegated Regulation (EU) No 811/2013 aimed to be covered .....</b> |   | <b>130</b> |
| <b>Annex ZD (informative) Relationship between this European Standard and the ecodesign requirements of Commission Regulation (EU) 2015/1095 aimed to be covered .....</b>                    |   | <b>132</b> |