DIN EN 14624:2020-08 (E)

Performance of portable locating leak detectors and of fixed gas detectors for all refrigerants

Contents

Page

European foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 7

4 Symbols and abbreviations 10

5 General requirements for all portable locating leak detectors and fixed gas detectors -- Refrigerant gas type(informative) 10

6 Specific requirements for portable locating leak detectors 11
6.1 Detection limits 11
6.1.1 General 11
6.1.2 Static detection limit - the leak detector probe is stationary 11
6.1.3 Dynamic detection limit - the leak detector probe is moving 11
6.1.4 Dynamic detection limit in a contaminated environment 11
6.2 Response time 11
6.3 Recovery time 11
6.4 Calibration frequency and procedure 11

7 Test apparatus for portable leak detectors 11
7.1 General 11
7.2 Calibration leaks 12
7.3 Measuring distance 12
7.4 Apparatus no. 1: detector probe stationary at the orifice of calibration leak 12
7.5 Apparatus no. 2: detector probe moved with defined speed and distance in front of a calibration leak 12
7.6 Apparatus no. 3a: Chamber with monitored concentration 14

8 Performance tests of portable leak detectors 15
8.1 General 15
8.2 Test no. 1: Static detection limits 15
8.3 Test no. 2: Dynamic detection limits 15
8.4 Test no. 3 Dynamic detection limit in a contaminated environment 16
8.5 Test no. 4: Response time 16
8.6 Test no. 5: Recovery time 16

9 Portable leak detector characteristics, reporting of test results and requirements 17
9.1 Reporting of test result 17
9.2 Minimum product requirements 17

10 Service and maintenance -- Portable locating leak detectors -- Periodic check and calibration 18

11 Technical specification and product information -- Portable locating leak detectors 18

12 Specific requirements for fixed gas detectors 18
12.1 General 18
12.2 Suitability 19
12.3 Function of gas detector 19
12.4 Ambient conditions, temperature and humidity 19
12.5 Typical measuring ranges and thresholds 20
12.6 Accuracy and performance 21
12.7 Response time 21

13 Test apparatus for fixed gas detectors 22
13.1 General 22
13.2 Apparatus no. 3b: Chamber with monitored concentration 22
13.3 Apparatus no. 4: Calibration gas with specific concentration 23
13.4 Apparatus no. 5: Calibration gas for aspirated systems 24

14 Performance tests of gas detector 24
14.1 General 24
14.2 Test conditions -- Temperature and humidity 24
14.3 Test methods 25
14.3.1 General 25
14.3.2 Test of accuracy and thresholds 25
14.3.3 Test of response time 25

15 Fixed gas detector characteristics, reporting of test results -- Reporting of test results ... 25

16 Service and maintenance -- Fixed gas detectors 25
16.1 Expected sensor lifecycle 25
16.2 Periodic check and calibration 25

17 Technical specification and product information - Fixed gas detectors 26

Annex A (informative) Conversion factors of leakage rate units 27

Annex B (informative) Correlation between test gas concentration and leakage rate 28

B.1 EXAMPLE 1a: Conversion of a concentration increase in a hood to a total leakage volume flow rate (pV-throughput) 28
B.2 EXAMPLE 1b: Concentration increase due to a small leak in a voluminous room 28
B.3 EXAMPLE 2: Conversion of a leakage rate (pV-throughput) into a mass flow rate 29
B.4 EXAMPLE 3:Calculation of the concentrations of tracer gas to be detected in front of a leak with specified leakage rate 30

Annex C (informative) Guidelines for application of Fixed Gas Detectors 32

Annex D (informative) Calculation of gas concentration from kg/m3 to ppm 33

Annex E (informative) Selectivity, cross interference and potential contaminants 34

Bibliography 36