

DIN EN 13771-2:2007-11 (En glisch)

Compressors and condensing units for refrigeration - Performance testing and test methods - Part 2: Condensing units

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms, definitions and symbols | 5 |
| 3.1 | Terms and definitions | 5 |
| 3.2 | Symbols | 6 |
| 3.3 | Refrigerant circuit state points | 8 |
| 4 | General requirements | 9 |
| 4.1 | Test equipment | 9 |
| 4.2 | Calculation methods | 9 |
| 4.2.1 | Principle | 9 |
| 4.2.2 | Specific enthalpy | 9 |
| 4.2.3 | Refrigerant mass flow | 9 |
| 4.2.4 | Power absorbed | 9 |
| 4.2.5 | Basic equations | 9 |
| 4.3 | Requirements for the selection of test methods | 10 |
| 4.4 | Test procedure | 10 |
| 4.4.1 | General | 10 |
| 4.4.2 | Steady working conditions | 10 |
| 4.4.3 | Recording of measured data | 10 |
| 4.5 | Pressure and temperature measuring points | 11 |
| 4.6 | Oil circulation | 11 |
| 4.7 | Refrigerant composition | 11 |
| 4.8 | Calibration and requirements regarding measurement uncertainty | 11 |
| 4.8.1 | Calibration of calorimeters for methods A, B and C | 11 |
| 4.8.2 | Determination of the refrigerating capacity | 12 |
| 4.8.3 | Determination of the power absorbed by the condensing unit | 12 |
| 4.8.4 | Measuring instruments | 12 |
| 4.9 | Source of refrigerant data | 13 |
| 4.10 | Allowable deviations from the basic test conditions | 13 |
| 4.11 | Additional information | 14 |
| 5 | Test methods | 14 |
| 5.1 | General | 14 |
| 5.2 | List of test methods | 14 |
| 5.2.1 | Calorimetric methods | 14 |
| 5.2.2 | Flow meter methods | 15 |
| 5.3 | Method A: secondary fluid calorimeter on the suction side | 15 |
| 5.3.1 | Description | 15 |
| 5.3.2 | Calibration | 15 |
| 5.3.3 | Test procedure | 16 |
| 5.3.4 | Requirements | 16 |
| 5.3.5 | Determination of refrigerant mass flow | 16 |
| 5.4 | Method B: dry system refrigerant calorimeter on the suction side | 16 |
| 5.4.1 | Description | 16 |
| 5.4.2 | Calibration | 17 |
| 5.4.3 | Test procedure | 17 |

| | | |
|-------|---|----|
| 5.4.4 | Requirements | 17 |
| 5.4.5 | Determination of refrigerant mass flow | 17 |
| 5.5 | Method C: water-cooled condenser on the discharge side | 18 |
| 5.5.1 | Description | 18 |
| 5.5.2 | Calibration | 18 |
| 5.5.3 | Test procedure | 18 |
| 5.5.4 | Requirements | 19 |
| 5.5.5 | Determination of refrigerant mass flow | 19 |
| 5.6 | Method D: refrigerant vapour flow meter on the suction side | 19 |
| 5.6.1 | Description | 19 |
| 5.6.2 | Test procedure | 19 |
| 5.6.3 | Requirements | 19 |
| 5.6.4 | Determination of refrigerant mass flow | 20 |
| 5.7 | Method E: refrigerant flow meter in the liquid line | 20 |
| 5.7.1 | Description | 20 |
| 5.7.2 | Test procedure | 20 |
| 5.7.3 | Requirements | 21 |
| 5.7.4 | Determination of the refrigerant mass flow | 21 |
| 6 | Determination of the power absorbed by the condensing unit | 21 |
| 6.1 | General | 21 |
| 6.1.1 | Introduction | 21 |
| 6.1.2 | Measurement for condensing units where the motor is not an integral part of the unit | 21 |
| 6.1.3 | Measurement for condensing units where the motor is an integral part of the condensing unit | 21 |
| 6.1.4 | Measurement of the power absorbed by the auxiliary components | 22 |
| 6.2 | Calculation | 22 |
| 7 | Test report | 22 |
| 7.1 | General | 22 |
| 7.2 | General information in the test report | 22 |
| 7.3 | Basic data | 22 |
| 7.4 | Test results | 23 |
| 7.5 | Additional information | 23 |
| | Bibliography | 25 |