

ISO/CIE 19476:2014-06 (E)

Characterization of the performance of illuminance meters and luminance meters

Contents

Page

| | |
|--|-----|
| Foreword..... | vii |
| 1 Scope | 1 |
| 2 Normative References | 1 |
| 3 Definitions | 2 |
| 3.1 General Definitions | 2 |
| 3.2 Quality Indices..... | 4 |
| 4 Calibration..... | 7 |
| 4.1 Conditions | 7 |
| 4.2 Illuminance Meters | 7 |
| 4.2.1 General | 7 |
| 4.2.2 (Planar) Illuminance E | 7 |
| 4.2.3 Spherical Illuminance E_0 | 8 |
| 4.2.4 Cylindrical Illuminance E_c | 8 |
| 4.2.5 Semi-Cylindrical Illuminance E_{sc} | 8 |
| 4.2.6 Semi-Spherical Illuminance $E_{2\pi}$ | 9 |
| 4.3 Luminance Meters | 9 |
| 4.4 Calibration Uncertainties..... | 9 |
| 4.5 Initial Adjustment..... | 10 |
| 4.6 Checking of Photometers | 10 |
| 5 Properties of Illuminance Meters and Luminance Meters | 11 |
| 5.1 General Considerations | 11 |
| 5.2 Spectral Properties | 11 |
| 5.2.1 General | 11 |
| 5.2.2 Measurement..... | 11 |
| 5.2.3 Luminous Responsivity | 12 |
| 5.2.4 Relative Luminous Responsivity and Spectral Mismatch Correction Factor..... | 12 |
| 5.2.5 Colour Correction Factor and Mismatch Exponent..... | 13 |
| 5.2.6 Specific Mismatch Index | 13 |
| 5.2.7 General $V(\lambda)$ Mismatch Index f_1' | 13 |
| 5.3 UV Response | 14 |
| 5.3.1 General | 14 |
| 5.3.2 Measurement..... | 14 |
| 5.3.3 Characterization..... | 15 |
| 5.4 IR Response..... | 16 |
| 5.4.1 General | 16 |
| 5.4.2 Measurement..... | 16 |
| 5.4.3 Characterization..... | 16 |

| | | |
|--------|--|----|
| 5.5 | Directional Response for Illuminance Meters | 17 |
| 5.5.1 | General | 17 |
| 5.5.2 | Measurement..... | 17 |
| 5.5.3 | Characterization for (Planar) Illuminance Meters..... | 17 |
| 5.5.4 | Characterization for Spherical Illuminance Meter | 18 |
| 5.5.5 | Characterization for Cylindrical Illuminance Meter..... | 19 |
| 5.5.6 | Characterization for Semi-Cylindrical Illuminance Meter..... | 20 |
| 5.5.7 | Characterization for Semi-Spherical Illuminance Meter | 21 |
| 5.6 | Directional Response for Luminance Meter | 22 |
| 5.6.1 | General | 22 |
| 5.6.2 | Measurement..... | 22 |
| 5.6.3 | Characterization..... | 22 |
| 5.6.4 | Measurement of the Effect of the Surrounding Field | 24 |
| 5.7 | Linearity | 25 |
| 5.7.1 | General | 25 |
| 5.7.2 | Measurement..... | 25 |
| 5.7.3 | Characterization..... | 25 |
| 5.8 | Display-Unit..... | 26 |
| 5.8.1 | General | 26 |
| 5.8.2 | Characterization..... | 26 |
| 5.9 | Fatigue..... | 27 |
| 5.9.1 | General | 27 |
| 5.9.2 | Measurement..... | 27 |
| 5.9.3 | Characterization..... | 27 |
| 5.10 | Temperature..... | 27 |
| 5.10.1 | General | 27 |
| 5.10.2 | Measurement..... | 28 |
| 5.10.3 | Characterization..... | 28 |
| 5.11 | Humidity Resistance | 28 |
| 5.11.1 | General | 28 |
| 5.11.2 | Measurement..... | 28 |
| 5.11.3 | Characterization..... | 29 |
| 5.12 | Modulated Light..... | 29 |
| 5.12.1 | General | 29 |
| 5.12.2 | Measurement..... | 29 |
| 5.12.3 | Characterization..... | 30 |
| 5.13 | Polarization Dependence | 30 |
| 5.13.1 | General | 30 |
| 5.13.2 | Measurement..... | 30 |
| 5.13.3 | Characterization..... | 31 |
| 5.14 | Spatial Non-Uniformity Response..... | 31 |
| 5.14.1 | General | 31 |
| 5.14.2 | Measurement..... | 31 |
| 5.14.3 | Characterization..... | 31 |
| 5.15 | Range Change | 32 |
| 5.15.1 | General | 32 |
| 5.15.2 | Measurement..... | 32 |
| 5.15.3 | Characterization..... | 32 |

| | | |
|--------|--|----|
| 5.16 | Focusing Distance (luminance meter only) | 32 |
| 5.16.1 | General | 32 |
| 5.16.2 | Measurement | 33 |
| 5.16.3 | Characterization | 33 |
| 6 | Acronyms | 33 |

| | | |
|-----------------------|--|----|
| Annex A (normative) | Sources and Filters Used for the Determination of the UV and IR Response | 34 |
| Annex B (informative) | General Comments | 36 |
| B.1 | General | 36 |
| B.2 | Quality Indices | 36 |
| B.2.1 | $V(\lambda)$ Mismatch f'_1 | 36 |
| B.2.2 | UV Response f_{UV} | 36 |
| B.2.3 | IR Response f_{IR} | 36 |
| B.2.4 | Cosine Response f_2 (illuminance meter only) | 36 |
| B.2.5 | Directional Response $f_{2,g}$ and Surround Field $f_{2,u}$ (luminance meter only) | 37 |
| B.2.6 | Linearity f_3 | 37 |
| B.2.7 | Display-Unit f_4 | 37 |
| B.2.8 | Fatigue f_5 | 37 |
| B.2.9 | Temperature Dependence $f_{6,T}$ | 37 |
| B.2.10 | Humidity Resistance $f_{6,H}$ | 37 |
| B.2.11 | Modulated Light f_7 | 37 |
| B.2.12 | Polarization f_8 | 37 |
| B.2.13 | Spatial Non-Uniformity Response f_9 | 38 |
| B.2.14 | Range Change f_{11} | 38 |
| B.2.15 | Focusing Distance f_{12} (luminance meter only) | 38 |