

DIN EN 15193-1:2017-10 (E)

Energy performance of buildings - Energy requirements for lighting - Part 1: Specifications, Module M9

Contents		Page
European foreword		5
Introduction		6
1	Scope	9
2	Normative references	10
3	Terms and definitions	11
4	Symbols and abbreviations	12
4.1	Symbols and units	12
4.2	Subscripts	18
4.3	Abbreviations	18
5	Brief description of the method(s) and routing	18
5.1	Output of the method 1 - Comprehensive method	18
5.2	Optional methods	19
5.2.1	Method 2 - Quick calculation method	19
5.2.2	Method 3 - Direct metering method	19
5.3	Selection criteria between the methods	19
6	Method 1 - Calculation of the energy required for lighting	20
6.1	Output data	20
6.2	Calculation time interval and calculation period	20
6.3	Input data	20
6.3.1	Lighting system data	20
6.3.2	Product data	21
6.3.3	System design data	22
6.3.4	Operating conditions	22
6.3.5	Constants and physical data	23
6.4	Calculation procedure	23
6.4.1	Applicable time step	23
6.4.2	Operating conditions calculation	23
6.4.3	Energy for lighting calculation	23
6.5	Expenditure factors for lighting systems	27
7	Method 2 - Quick calculation of the energy required for lighting	30
7.1	Output data	30
7.2	Calculation time steps	30
7.3	Input data	30
7.3.1	Lighting system data	30
7.3.2	Luminaire data	31
7.3.3	System design data	31
7.3.4	Operating conditions	31
7.3.5	Constants and physical data	31
7.4	Calculation procedure	31
7.4.1	Applicable time step	31
7.4.2	Operating conditions calculation	31
7.4.3	Energy calculation	31
7.5	Expenditure factors for lighting systems	34

8	Method 3 - Metered energy used for lighting	34
8.1	Output data	34
8.2	Calculation time steps	35
8.3	Input data	35
8.4	Calculation procedure of annual energy	35
9	Quality control	35
9.1	Method 1	35
9.2	Method 2	36
9.3	Method 3	36
10	Compliance check	36
10.1	General	36
10.2	Method 1	36
10.3	Method 2	36
10.4	Method 3	36
Annex A (normative) Input and method selection data sheet -- Template		37
A.1	General	37
A.2	System design data	37
A.2.1	General	37
A.2.2	Standby energy density	38
A.2.3	Annual operating hours	38
A.2.4	Daylight supply factor for vertical façades	38
A.2.5	Daylight supply factor for roof lights	38
A.2.6	Absence factor (FA) for rooms in building types	38
A.2.7	Example constant illuminance dependency factors (FC)	39
A.2.8	Installed power for residential buildings	39
A.2.9	Useful areas in residential buildings	40
Annex B (informative) Input and method selection data sheet -- Default choices		41
B.1	General	41
B.2	Method 1	41
B.2.1	Luminaire description data	41
B.2.2	Luminaire technical data tables	41
B.2.3	System design data	42
B.3	Method 2	42
B.3.1	Luminaire description data	42
B.3.2	Luminaire technical data tables	42
B.3.3	System design data	42
B.4	Method 3	49
Annex C (normative) Simplified Method for Installed Power Estimation		50
C.1	General	50
C.2	Installed power assessment for non-residential buildings	50
C.3	Installed power assessment for residential buildings	52
Annex D (normative) Assessment of the installed power for lighting systems in existing buildings .		53
Annex E (normative) Occupancy estimation		54
Annex F (normative) Daylight availability		59
F.1	General	59
F.2	Building segmentation: Spaces benefiting from daylight	61
F.3	Daylight supply factor for vertical façades	63
F.3.1	Daylight factor classification	63
F.3.2	Daylight supply factor	68

F.4	Daylight supply factor for roof lights	80
F.4.1	General	80
F.4.2	Daylight availability factor	80
F.4.3	Daylight supply factor	85
F.4.4	Relative times, shading activated/ not activated for roof lights	86
F.4.5	Daylight supply factors as function of the daylight availability classification	88
F.5	Daylight Responsive Control Systems	91
F.6	Monthly evaluation method	93
F.7	Determination of daytime and night time hours	94
F.8	Comprehensive calculation	96
F.9	Collection of input data required for daylight calculations	97
Annex G (normative) Constant illuminance		98
G.1	General	98
G.2	Constant illuminance factor (Fc)	98
G.3	Constant lumen output system (CLO)	99
Annex H (normative) Standby system energy requirements		100
H.1	Emergency lighting luminaire standby charging power (Pem)	100
H.2	Lighting controls standby power (Ppc)	100
Bibliography		101