ISO/CIE 22012:2019 (E)

Light and lighting — Maintenance factor determination — Way of working

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Symbols and units

5 Influencing factors

- 5.1 Luminaire and/or light source characteristics
- 5.2 Recoverable external factors
- 5.3 Non-recoverable external factors
- 5.4 Maintenance period, cleaning, replacement and surface refurbishment interval

6 Maintenance factor determination

- 6.1 Basic description of the method
- 6.2 Luminous flux factor
- 6.2.1 Luminous flux factor determination — General
- 6.2.2 Luminous flux factor determination — Special case: Constant light output (CLO)
- 6.3 Survival factor
- 6.3.1 Survival factor description
- 6.3.2 Spot replacement regime
- 6.3.3 Group replacement regime
- 6.3.4 Regime combinations
- 6.4 Luminaire maintenance factor
- 6.4.1 Luminaire maintenance factor description
- 6.4.2 Indoor luminaires
- 6.4.3 Outdoor luminaires
- 6.5 Surface maintenance factor

7 Use of the maintenance factor

- 7.1 Lighting design using the maintenance factor
- 7.2 Documentation
- 7.2.1 Documentation of maintenance factor determination
- 7.2.2 Documentation of maintenance schedules
- 7.3 Lighting verification using the maintenance factor

Annex A (informative) Maintenance factor determination examples

- A.1 Example 1: Parking area project 100 000 h, using spot replacement
- A.2 Example 2: Urban street project 100 000 h, with CLO, using spot replacement
- A.3 Example 3: Office project 25 000 h, using spot replacement
- A.4 Example 4: Warehouse project, 10 years, using group replacement

Annex B (informative) Luminous flux factor fLF tables (Typical examples)

Annex C (informative) Luminaire maintenance factor fLM determination examples

- C.1 Indoor luminaires
- C.2 Outdoor luminaires

Annex D (informative) Surface maintenance factor fSM examples

Page count: 12