ISO 19454:2019 (E)

Building environment design — Indoor environment — Daylight opening design for sustainability principles in visual environment

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Fundamentals

- 4.1 General
- 4.2 General principles of sustainability
- 4.3 Project information
- 4.4 Framework of generation and verification
- 4.5 Framework of documentation at approval
- 4.6 Harmonization of architectural and daylight opening design

5 Design elements of daylight openings

- 5.1 General
- 5.2 Matrix of aspects of daylight opening design
- 5.3 Daylight opening ratio to the wall area
- 5.4 Daylight opening ratio to the floor area
- 5.5 Levels of indoor daylight and the extent of sunlight
- 5.6 Quality of views to exterior
- 5.7 Daylight control systems in the building

6 Design process of daylight openings

- 6.1 General
- 6.2 Stage I — Formulation of project definition
- 6.2.1 Project definition
- 6.2.2 Output — Document I
- 6.2.3 Evaluation I
- 6.2.4 Output — Approval of document I
- 6.2.5 Iteration
- 6.3 Stage II – Schematic design
- 6.3.1 General
- 6.3.2 Input
- 6.3.3 Output
- 6.3.4 Evaluation II
- 6.3.5 Approval of document II
- 6.4 Stage III – Detailed design
- 6.4.1 General
- 6.4.2 Input
- 6.4.3 Output – Document IIIa
- 6.4.4 Analysis
- 6.4.5 Output – Document IIIb
- 6.4.6 Evaluation III
- 6.4.7 Approval of documents IIIa and IIIb
- 6.4.8 Iteration into detail design
- 6.5 Stage IV – Final design
- 6.5.1 General
- 6.5.2 Commissioning documents

6.5.3 Cost estimation
6.5.4 Output: the final documents

Annex A (normative) Flow diagram of the design process

Annex B (informative) Basic architectural forms of the daylight opening

B.1 Side lighting
B.2 Top lighting

Annex C (informative) Matrix of aspects of daylight opening design

Annex D (informative) Matrix of output required to satisfy daylight opening design

Page count: 26