

# DIN 5034-6:2007-02 (E)

## Daylight in interiors - Part 6: Simplified determination of suitable dimensions for rooflights

---

| <b>Contents</b>  |  | <b>Page</b> |
|--|--|-------------|
| Foreword .....   |  | 3           |
| Introduction .....   |  | 4           |
| 1 Scope .....  |  | 4           |
| 2 Normative references .....   |  | 4           |
| 3 Symbols .....  |  | 5           |
| 4 Daylight factor .....  |  | 6           |
| 5 Simplified assumptions .....   |  | 7           |
| 5.1 Obstructions .....   |  | 7           |
| 5.2 Transmittance .....  |  | 7           |
| 5.3 Reduction factor for frames, sash bars, etc .....  |  | 7           |
| 5.4 Dirt .....   |  | 8           |
| 5.5 Reflectance of internal room surfaces .....  |  | 9           |
| 6 Calculation of auxiliary parameters .....  |  | 9           |
| 6.1 Effect of rooflight wells .....  |  | 9           |
| 6.2 Effect of the shape of rooflights .....  |  | 10          |
| 6.3 Effect of finite room dimensions .....   |  | 10          |
| 7 Calculation of the necessary rooflight rough opening area .....  |  | 12          |
| Bibliography .....   |  | 13          |
| Figures Figure 1 -- Schematic overview for the explanation of uniformities $g_1$ and $g_2$ .....   |  | 6           |
| Figure 2 -- Reduction factor $k_e$ to account for the effects of the light well at different angles of inclination $W$ and a reflectance of the well walls of $S = 0,55$ in relation to the well index $w$ .....   |  | 8           |
| Figure 3 -- Overview of the geometric parameters of a rooflight well .....   |  | 10          |
| Figure 4 -- Corrections $a$ and $b$ to account for the finite room length $a$ and width $b$ in relation to angles $\alpha$ and $\beta$ , which are given by the ratio of one-half the room length or width to the distance between the working plane and the ceiling ..... |  | 11          |
| Figure 5 -- Example showing the dimensions necessary for determining corrections for finite room lengths and widths .....  |  | 11          |
| Tables Table 1 -- Relation between reduction factor $k_2$ and dirt load on the glazing (guidance values) Table 2 -- Reduction factor $k_4$ to account for the shape of rooflights .....  |  | 10          |