

# DIN 5034-6:2007-02 (E)

## Daylight in interiors - Part 6: Simplified determination of suitable dimensions for rooflights

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
Introduction .....		4
1 Scope .....		4
2 Normative references .....		4
3 Symbols .....		5
4 Daylight factor .....		6
5 Simplified assumptions .....		7
5.1 Obstructions .....		7
5.2 Transmittance .....		7
5.3 Reduction factor for frames, sash bars, etc .....		7
5.4 Dirt .....		8
5.5 Reflectance of internal room surfaces .....		9
6 Calculation of auxiliary parameters .....		9
6.1 Effect of rooflight wells .....		9
6.2 Effect of the shape of rooflights .....		10
6.3 Effect of finite room dimensions .....		10
7 Calculation of the necessary rooflight rough opening area .....		12
Bibliography .....		13
Figures Figure 1 -- Schematic overview for the explanation of uniformities $g_1$ and $g_2$ .....		6
Figure 2 -- Reduction factor $k_e$ to account for the effects of the light well at different angles of inclination $W$ and a reflectance of the well walls of $S = 0,55$ in relation to the well index $w$ .....		8
Figure 3 -- Overview of the geometric parameters of a rooflight well .....		10
Figure 4 -- Corrections $a$ and $b$ to account for the finite room length $a$ and width $b$ in relation to angles $\alpha$ and $\beta$ , which are given by the ratio of one-half the room length or width to the distance between the working plane and the ceiling .....		11
Figure 5 -- Example showing the dimensions necessary for determining corrections for finite room lengths and widths .....		11
Tables Table 1 -- Relation between reduction factor $k_2$ and dirt load on the glazing (guidance values) Table 2 -- Reduction factor $k_4$ to account for the shape of rooflights .....		10