

ISO 8655-7:2022-04 (E)

Piston-operated volumetric apparatus - Part 7: Alternative measurement procedures for the determination of volume

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	General requirements	2
4.1	Metrological confirmation	2
4.2	Uncertainty of measurement	2
4.3	Operator qualification	2
5	Performance requirements	3
5.1	Performance tolerances	3
5.2	Operator impact	3
6	Test conditions	3
6.1	General	3
6.2	Test equipment	3
6.3	Test room, environmental conditions	3
6.4	Test volumes	4
6.4.1	Fixed volume POVA	4
6.4.2	Adjustable volume POVA	4
6.5	Number of measurements per test volume	4
6.6	Test liquids	5
7	Evaluation	5
7.1	Mean volume	5
7.2	Systematic error of measurement	5
7.3	Random error of measurement	6
8	Test methods	6
8.1	General	6
8.2	Gravimetric method	7
8.3	Dual-dye ratiometric photometric method	7
8.4	Single dye photometric method	8
8.5	Hybrid photometric/gravimetric method for multichannel POVA	8
8.6	Titration method	8
8.7	Batch testing	8
9	Dispense procedures	8
9.1	General	8
9.2	Preparation	9
9.3	Single-channel air displacement pipettes (in accordance with ISO 8655-2)	9
9.3.1	General	9
9.3.2	Test cycle	9
9.4	Multi-channel pipettes (in accordance with ISO 8655-2)	10
9.5	Positive displacement pipettes (in accordance with ISO 8655-2)	11

9.6	Burettes (in accordance with ISO 8655-3)	11
9.7	Dilutors (in accordance with ISO 8655-4)	12
9.7.1	General	12
9.7.2	Test cycle	12
9.8	Dispensers (in accordance with ISO 8655-5)	13
9.9	Syringes (in accordance with ISO 8655-9)	13
9.9.1	General	13
9.9.2	Test cycle	13
10	Reporting of results	14
ISO 8655-7:2022(E) Annex A (normative) Gravimetric procedure		16
Annex B (normative) Dual-dye ratiometric photometric procedure		21
Annex C (normative) Single dye photometric procedure		29
Annex D (normative) Photometric/gravimetric hybrid procedure		33
Annex E (normative) Titrimetric procedure		41
Annex F (normative) Conversion of liquid mass to volume		45
Bibliography		48