ISO/TS 6417:2025-06 (E)

Microfluidic pumps - Symbols and performance communication

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Symbols 2

5 Standard Datasheets 2
5.1 Naming 2
5.2 Schematic/symbol 2
5.3 Technology characteristics 3
5.3.1 General 3
5.3.2 Actuation Type 3
5.3.3 Requirement of additional consumables 3
5.3.4 Wetted material 3
5.3.5 Reversible flow 3
5.3.6 Closed loop possibility 3
5.3.7 Operational lifetime 3
5.3.8 Reusable 3
5.4 General working conditions 4
5.4.1 Maximum pressure delivered 4
5.4.2 Ability to work in an incubator 4
5.4.3 Self-priming 4
5.4.4 Lifetime until out of accuracy 4
5.4.5 Self-heating 4
5.4.6 Sound level 4
5.4.7 Certifications 4
5.4.8 Back pressure 4
5.5 Electrical characteristics 4
5.5.1 Power supply 4
5.5.2 Electromagnetic compatibility 4
5.6 Mechanical characteristics 5
5.6.1 Internal volume 5
5.6.2 Dimension - Size 5
5.6.3 Weight 5
5.6.4 Working pressure 5
5.6.5 Integration level 5
5.6.6 Outlet/Inlet connector and accessories 5
5.7 Flow characteristics 5
5.7.1 General 5
5.7.2 Standard deviation (stability) 5
5.7.3 Response time 5
5.7.4 Open state fluidic resistance 6
5.7.5 Flow rate range 6

Annex A (informative) Datasheet and symbols for pumps 7

Bibliography 14