

# ISO/TS 6417:2025-06 (E)

## Microfluidic pumps - Symbols and performance communication

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Symbols .....	2
5	Standard Datasheets .....	2
5.1	Naming .....	2
5.2	Schematic/symbol .....	2
5.3	Technology characteristics .....	3
5.3.1	General .....	3
5.3.2	Actuation Type .....	3
5.3.3	Requirement of additional consumables .....	3
5.3.4	Wetted material .....	3
5.3.5	Reversible flow .....	3
5.3.6	Closed loop possibility .....	3
5.3.7	Operational lifetime .....	3
5.3.8	Reusable .....	3
5.4	General working conditions .....	4
5.4.1	Maximum pressure delivered .....	4
5.4.2	Ability to work in an incubator .....	4
5.4.3	Self-priming .....	4
5.4.4	Lifetime until out of accuracy .....	4
5.4.5	Self-heating .....	4
5.4.6	Sound level .....	4
5.4.7	Certifications .....	4
5.4.8	Back pressure .....	4
5.5	Electrical characteristics .....	4
5.5.1	Power supply .....	4
5.5.2	Electromagnetic compatibility .....	4
5.6	Mechanical characteristics .....	5
5.6.1	Internal volume .....	5
5.6.2	Dimension - Size .....	5
5.6.3	Weight .....	5
5.6.4	Working pressure .....	5
5.6.5	Integration level .....	5
5.6.6	Outlet/Inlet connector and accessories .....	5
5.7	Flow characteristics .....	5
5.7.1	General .....	5
5.7.2	Standard deviation (stability) .....	5
5.7.3	Response time .....	5
5.7.4	Open state fluidic resistance .....	6
5.7.5	Flow rate range .....	6
Annex A (informative)	Datasheet and symbols for pumps .....	7
Bibliography .....		14