ISO 12742:2007-07 (E)

Copper, lead, and zinc sulfide concentrates - Determination of transportable moisture limits - Flow-table method

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Principle 1

4 Apparatus 1

5 Sampling and sample preparation 2
5.1 General 2
5.2 Laboratory sample 3
5.3 Sample preparation 3

6 Procedure 3
6.1 General 3
6.2 Preparation of test portions 4
6.2.1 General 4
6.2.2 Filling the mould 4
6.2.3 Tamping pressure 4
6.2.4 Tamping procedure 5
6.2.5 Removal of the mould 5
6.2.6 Dropping the flow table 5
6.3 Identification of the flow state 5
6.4 Preliminary flow moisture point 7
6.4.1 Preparation of test portion 7
6.4.2 Determination of preliminary flow moisture point 7
6.4.3 Addition of water for preliminary flow moisture point test 8
6.5 Main flow moisture point determination 8
6.5.1 Preparation of test portions 8
6.5.2 Determination of main flow moisture point 8
6.5.3 Addition of water for main flow moisture point determination 8
6.6 Graphical method 8
6.6.1 Preparation of test portions 8
6.6.2 Determination of flow moisture point 9
6.7 Moisture determination 9

7 Expression of results 9
7.1 Main flow moisture point 9
7.2 Flow moisture point determined by the graphical method 9

8 Validation of main flow moisture point 10

9 Test report 10

Annex A (normative) Description of equipment used to determine TML 11

Bibliography 18