

DIN EN 755-1:2008-06 (E)

Aluminium and aluminium alloys - Extruded rod/bar, tube and profiles - Part 1: Technical conditions for inspection and delivery

Contents		Page
Foreword		3
1	Scope	5
2	Normative references	5
3	Terms and definitions	6
4	Ordering information	6
5	Requirements	8
5.1	Production and manufacturing processes	8
5.2	Quality control	8
5.3	Chemical composition limits	8
5.4	Mechanical properties	8
5.5	Freedom from surface defects	8
5.6	Tolerances on dimensions and form	9
5.7	Stress corrosion cracking resistance	9
5.8	Additional requirements	9
6	Test procedures	9
6.1	Sampling	9
6.2	Test methods	11
6.3	Re-tests	12
7	Inspection documents	12
8	Marking of products	12
9	Packaging	13
10	Arbitration	13
Annex A (normative)	Location of test pieces	14
A.1	Round, square and hexagonal bar	14
A.1.1	For diameter (D) or width across flats (S) up to and including 40 mm:	14
A.1.2	For diameter (D) or width across flats (S) over 40 mm;	14
A.2	Rectangular bar	15
A.2.1	For thickness up to and including 12,5 mm:	15
A.2.2	For thickness (T) over 12,5 mm and up to and including 40 mm:	15
A.2.3	For thickness (T) exceeding 40 mm:	15
A.3	Tube	15
A.4	Profiles	16
A.4.1	For thickness up to and including 12,5 mm:	16
A.4.2	For thickness over 12,5 mm and up to and including 40 mm:	16
A.4.3	For thickness exceeding 40 mm:	16
Annex B (normative)	Resistance to stress-corrosion cracking for alloy EN AW-7075 in tempers T73, T73510 and T73511 - Electrical conductivity	17
Bibliography		18