

# DIN EN ISO 8049:2016-12 (E)

## Ferronickel shot - Sampling for analysis (ISO 8049:2016)

---

| <b>Contents</b>   | <b>Page</b> |
|---|-------------|
| <b>European foreword</b> .....  | <b>3</b>    |
| <b>Foreword</b> .....   | <b>4</b>    |
| <b>1 Scope</b> .....  | <b>5</b>    |
| <b>2 Normative references</b> .....   | <b>5</b>    |
| <b>3 Form and packaging of product</b> .....  | <b>5</b>    |
| <b>4 Principle</b> .....  | <b>5</b>    |
| <b>5 Taking of the primary sample and then of the intermediate sample</b> .....                               | <b>6</b>    |
| 5.1 Blended lots .....  | 6           |
| 5.1.1 Bulk sampling in the case of a suitable system for taking the primary sample .....                      | 6           |
| 5.1.2 Sampling of bulk material when no adequate primary sampling system is available .....                   | 7           |
| 5.1.3 Sampling of a drum-packed lot .....   | 7           |
| 5.1.4 Sampling of a container-packed lot .....  | 7           |
| 5.2 Particular case of a lot made up of one single heat .....   | 9           |
| <b>6 Treatment of the intermediate sample and taking of the secondary sample</b> .....                        | <b>9</b>    |
| 6.1 General .....   | 9           |
| 6.2 Blended lot .....   | 9           |
| 6.3 Lot made up of a single heat .....  | 9           |
| <b>7 Remelting of the secondary sample</b> .....  | <b>9</b>    |
| <b>8 Use of small ingots (secondary increments)</b> .....   | <b>10</b>   |
| <b>Annex A (informative) Justification of the number of primary and secondary increments</b> .....            | <b>12</b>   |
| <b>Annex B (informative) Methods for taking a sample of size <i>N</i> in a supply of <i>M</i> items</b> ..... | <b>21</b>   |
| <b>Annex C (informative) Technical conditions for drilling and milling</b> .....                              | <b>25</b>   |
| <b>Bibliography</b> .....   | <b>33</b>   |