

DIN EN 12449:2016-11 (E)

Copper and copper alloys - Seamless, round tubes for general purposes

| Contents | | Page |
|-----------------|---|-------------|
| | European foreword | 4 |
| | Introduction | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | Designations | 7 |
| 4.1 | Material | 7 |
| 4.1.1 | General | 7 |
| 4.1.2 | Symbol | 7 |
| 4.1.3 | Number | 7 |
| 4.2 | Material condition | 7 |
| 4.3 | Product | 8 |
| 5 | Ordering information | 9 |
| 6 | Requirements | 10 |
| 6.1 | Composition | 10 |
| 6.2 | Mechanical properties | 10 |
| 6.3 | Dimensions and tolerances | 10 |
| 6.3.1 | General | 10 |
| 6.3.2 | Outside or inside diameter | 10 |
| 6.3.3 | Wall thickness | 10 |
| 6.3.4 | Fixed lengths | 11 |
| 6.3.5 | Tolerances on form | 11 |
| 6.4 | Surface quality | 11 |
| 6.5 | Technological requirements | 11 |
| 6.5.1 | Drift expanding | 11 |
| 6.5.2 | Residual stress level | 11 |
| 6.5.3 | Grain size | 11 |
| 6.5.4 | Freedom from defects | 12 |
| 7 | Sampling | 12 |
| 7.1 | General | 12 |
| 7.2 | Analysis | 12 |
| 7.3 | Mechanical tests and stress corrosion resistance test | 12 |
| 8 | Test methods | 12 |
| 8.1 | Analysis | 12 |
| 8.2 | Tensile test | 13 |
| 8.3 | Hardness test | 13 |
| 8.4 | Technological tests | 13 |
| 8.4.1 | Drift expanding test | 13 |
| 8.4.2 | Stress corrosion resistance test | 13 |
| 8.4.3 | Average grain size determination | 13 |
| 8.5 | Freedom from defects tests | 13 |
| 8.6 | Retests | 13 |
| 8.6.1 | Analysis, tensile, hardness, drift expanding and grain size tests | 13 |

| | | |
|-------|--|----|
| 8.6.2 | Stress corrosion resistance test | 14 |
| 8.7 | Rounding of results | 14 |
| 9 | Declaration of conformity and inspection documentation | 14 |
| 9.1 | Declaration of conformity | 14 |
| 9.2 | Inspection documentation | 14 |
| 10 | Marking, packaging, labelling | 14 |
| | Bibliography | 41 |
| | Figures Figure 1 -- Measurement of straightness | 40 |
| | Tables Table 1 -- Composition of copper | 15 |
| | Table 2 -- Composition of low alloyed copper alloys | 15 |
| | Table 3 -- Composition of copper-nickel alloys | 16 |
| | Table 4 -- Composition of copper-nickel-zinc alloys | 16 |
| | Table 5 -- Composition of copper-tin alloys | 16 |
| | Table 6 -- Composition of binary copper-zinc alloys | 17 |
| | Table 7 -- Composition of copper-zinc-lead alloys | 17 |
| | Table 8 -- Composition of complex copper-zinc alloys | 18 |
| | Table 9 -- Mechanical properties of copper and low alloyed copper alloys | 19 |
| | Table 10 -- Mechanical properties of copper-nickel alloys | 22 |
| | Table 11 -- Mechanical properties of copper-nickel-zinc alloys | 23 |
| | Table 12 -- Mechanical properties of copper-tin alloys | 24 |
| | Table 13 -- Mechanical properties of binary copper-zinc alloys | 27 |
| | Table 14 -- Mechanical properties of copper-zinc-lead alloys | 31 |
| | Table 15 -- Mechanical properties of complex copper-zinc alloys | 34 |
| | Table 16 -- Minimal elongation values for R250 (half hard) material condition tubes | 38 |
| | Table 17 -- Tolerances on diameter | 38 |
| | Table 18 -- Tolerances on wall thickness | 38 |
| | Table 19 -- Tolerances on fixed lengths, tubes in straight lengths | 39 |
| | Table 20 -- Tolerances on fixed lengths, tube in coils (not level wound) | 39 |
| | Table 21 -- Tolerances on diameter including deviation from circular form, tube in coils | 39 |
| | Table 22 -- Tolerances on straightness | 40 |
| | Table 23 -- Sampling rate | 40 |