

# DIN EN 755-1:2016-10 (E)

## Aluminium and aluminium alloys - Extruded rod/bar, tube and profiles - Part 1: Technical conditions for inspection and delivery

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
1	Scope .....	5
2	Normative references .....	5
3	Terms and definitions .....	6
4	Ordering information .....	6
5	Requirements .....	8
5.1	Production and manufacturing processes .....	8
5.2	Quality control .....	8
5.3	Chemical composition limits .....	8
5.4	Mechanical properties .....	8
5.5	Freedom from surface defects .....	9
5.6	Tolerances on dimensions and form .....	9
5.7	Stress corrosion cracking resistance .....	9
5.8	Additional requirements .....	9
6	Test procedures .....	9
6.1	Sampling .....	9
6.1.1	Samples for chemical analysis .....	9
6.1.2	Specimens for mechanical testing .....	10
6.1.3	Test pieces for tensile test .....	11
6.2	Test methods .....	11
6.2.1	Chemical composition limits .....	11
6.2.2	Tensile testing .....	11
6.2.3	Brinell hardness testing .....	11
6.2.4	Measurement of dimensions .....	11
6.2.5	Surface finish .....	12
6.2.6	Resistance to stress corrosion cracking .....	12
6.2.7	Additional tests .....	12
6.3	Re-tests .....	12
6.3.1	Chemical composition limits .....	12
6.3.2	Mechanical properties .....	12
6.3.3	Other properties .....	13
7	Inspection documents .....	13
8	Marking of products .....	13
9	Packaging .....	13
10	Arbitration .....	13
Annex A (normative) Location of test pieces .....		14
A.1	Round, square and hexagonal bar .....	14
A.1.1	For diameter (D) or width across flats (S) up to and including 40 mm .....	14
A.1.2	For diameter (D) or width across flats (S) over 40 mm .....	14

<b>A.2</b>	<b>Rectangular bar .....</b>	<b>15</b>
<b>A.2.1</b>	<b>For thickness up to and including 12,5 mm .....</b>	<b>15</b>
<b>A.2.2</b>	<b>For thickness (T) over 12,5 mm and up to and including 40 mm .....</b>	<b>15</b>
<b>A.2.3</b>	<b>For thickness (T) exceeding 40 mm .....</b>	<b>15</b>
<b>A.3</b>	<b>Tube .....</b>	<b>16</b>
<b>A.4</b>	<b>Profiles .....</b>	<b>16</b>
<b>A.4.1</b>	<b>For thickness up to and including 12,5 mm .....</b>	<b>16</b>
<b>A.4.2</b>	<b>For thickness over 12,5 mm and up to and including 40 mm .....</b>	<b>16</b>
<b>A.4.3</b>	<b>For thickness exceeding 40 mm .....</b>	<b>17</b>
<b>Annex B (normative)</b>	<b>Resistance to stress-corrosion cracking for alloy EN AW-7075 in tempers</b>	
	<b>T73, T73510 and T73511 - Electrical conductivity .....</b>	<b>18</b>
<b>Bibliography .....</b>		<b>19</b>