

# DIN EN 12166:2016-11 (E)

## Copper and copper alloys - Wire for general purposes

---

| <b>Contents</b>              |   | <b>Page</b> |
|------------------------------|---|-------------|
| European foreword .....      |   | 4           |
| Introduction .....           |   | 6           |
| <b>1</b>                     | <b>Scope .....</b>  | <b>7</b>    |
| <b>2</b>                     | <b>Normative references .....</b>   | <b>7</b>    |
| <b>3</b>                     | <b>Terms and definitions .....</b>  | <b>7</b>    |
| <b>4</b>                     | <b>Designation .....</b>  | <b>8</b>    |
| <b>4.1</b>                   | <b>Material .....</b>   | <b>8</b>    |
| <b>4.1.1</b>                 | <b>General .....</b>  | <b>8</b>    |
| <b>4.1.2</b>                 | <b>Symbol .....</b>   | <b>8</b>    |
| <b>4.1.3</b>                 | <b>Number .....</b>   | <b>8</b>    |
| <b>4.2</b>                   | <b>Material condition .....</b>   | <b>8</b>    |
| <b>4.3</b>                   | <b>Product .....</b>  | <b>8</b>    |
| <b>5</b>                     | <b>Ordering information .....</b>   | <b>10</b>   |
| <b>6</b>                     | <b>Requirements .....</b>   | <b>13</b>   |
| <b>6.1</b>                   | <b>Composition .....</b>  | <b>13</b>   |
| <b>6.2</b>                   | <b>Mechanical properties .....</b>  | <b>13</b>   |
| <b>6.3</b>                   | <b>Grain size .....</b>   | <b>13</b>   |
| <b>6.4</b>                   | <b>Dimensions and tolerances .....</b>  | <b>13</b>   |
| <b>6.4.1</b>                 | <b>Diameter or width across-flats .....</b>   | <b>13</b>   |
| <b>6.4.2</b>                 | <b>Shape tolerances for round wire .....</b>  | <b>13</b>   |
| <b>6.4.3</b>                 | <b>Corner and edge geometry (wire with square and rectangular cross-section only) .....</b> | <b>13</b>   |
| <b>6.5</b>                   | <b>Joins .....</b>  | <b>14</b>   |
| <b>6.6</b>                   | <b>Surface quality .....</b>  | <b>14</b>   |
| <b>7</b>                     | <b>Sampling .....</b>   | <b>14</b>   |
| <b>7.1</b>                   | <b>General .....</b>  | <b>14</b>   |
| <b>7.2</b>                   | <b>Analysis .....</b>   | <b>14</b>   |
| <b>7.3</b>                   | <b>Tensile, hardness and grain size tests .....</b>   | <b>15</b>   |
| <b>8</b>                     | <b>Test methods .....</b>   | <b>15</b>   |
| <b>8.1</b>                   | <b>Analysis .....</b>   | <b>15</b>   |
| <b>8.2</b>                   | <b>Tensile test .....</b>   | <b>15</b>   |
| <b>8.3</b>                   | <b>Hardness test .....</b>  | <b>15</b>   |
| <b>8.4</b>                   | <b>Estimation of average grain size .....</b>   | <b>16</b>   |
| <b>8.5</b>                   | <b>Retests .....</b>  | <b>16</b>   |
| <b>8.6</b>                   | <b>Rounding of results .....</b>  | <b>16</b>   |
| <b>9</b>                     | <b>Declaration of conformity and inspection documentation .....</b>                         | <b>16</b>   |
| <b>9.1</b>                   | <b>Declaration of conformity .....</b>  | <b>16</b>   |
| <b>9.2</b>                   | <b>Inspection documentation .....</b>   | <b>17</b>   |
| <b>10</b>                    | <b>Marking, packaging, labelling .....</b>  | <b>17</b>   |
| <b>Annex A (informative)</b> | <b>Position of wire cross-section within a coil, reel, spool or drum .....</b>              | <b>40</b>   |

|   |           |
|---|-----------|
| <b>Bibliography .....</b>   | <b>42</b> |
| <b>Figures Figure 1 -- Calculation of corner radii .....</b>  | <b>14</b> |
| <b>Figure A.1 -- Illustration of position of wire cross-section within the coil (bunched wound or stagger/traverse wound) .....</b> | <b>40</b> |
| <b>Figure A.2 -- Illustration of position of wire cross-section within the reel/spool/drum (stagger/traverse wound) .....</b>       | <b>40</b> |
| <b>Figure A.3 -- Illustration of position of wire cross-section within the coil (bunched wound or stagger/traverse wound) .....</b> | <b>41</b> |
| <b>Figure A.4 -- Illustration of position of wire cross-section within the reel/spool/drum (stagger/traverse wound) .....</b>       | <b>41</b> |
| <b>Tables Table 1 -- Composition of low alloyed copper alloys .....</b>   | <b>18</b> |
| <b>Table 2 -- Composition of copper-nickel-zinc alloys .....</b>  | <b>21</b> |
| <b>Table 3 -- Composition of copper-tin alloys .....</b>  | <b>21</b> |
| <b>Table 4 -- Composition of copper-zinc alloys .....</b>   | <b>22</b> |
| <b>Table 5 -- Composition of copper-zinc-lead alloys .....</b>  | <b>23</b> |
| <b>Table 6 -- Composition of complex copper-zinc alloys .....</b>   | <b>24</b> |
| <b>Table 7 -- Mechanical properties of wire of low alloyed copper alloys .....</b>  | <b>24</b> |
| <b>Table 8 -- Mechanical properties of wire of copper-nickel-zinc alloys .....</b>  | <b>27</b> |
| <b>Table 9 -- Mechanical properties of wire of copper-tin alloys .....</b>  | <b>29</b> |
| <b>Table 10 -- Mechanical properties of wire of copper-zinc alloys .....</b>  | <b>31</b> |
| <b>Table 11 -- Mechanical properties of wire of copper-zinc-lead alloys .....</b>   | <b>35</b> |
| <b>Table 12 -- Mechanical properties of wire of complex copper-zinc alloys .....</b>  | <b>36</b> |
| <b>Table 13 -- Grain size designations .....</b>  | <b>37</b> |
| <b>Table 14 -- Tolerances on diameter of round wire .....</b>   | <b>37</b> |
| <b>Table 15 -- Tolerances on width across-flats of square or regular polygonal wire .....</b>                                       | <b>38</b> |
| <b>Table 16 -- Tolerances on width and thickness of rectangular wire .....</b>  | <b>38</b> |
| <b>Table 17 -- Corner radii for square or rectangular wire .....</b>  | <b>39</b> |
| <b>Table 18 -- Sampling rate .....</b>  | <b>39</b> |