ISO 2107:2023-09 (E)

Aluminium and aluminium alloys - Wrought products - Temper designations

Contents

Page

Foreword ..... **iv**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Basic temper designations **2**
4.1 F — as fabricated 2
4.2 O — annealed 3
4.3 H — strain-hardened 3
4.4 W — solution heat-treated 3
4.5 T — precipitation hardened to produce stable tempers other than F, O or H 3

5 Subdivisions of O temper designations **3**
5.1 O1 — high-temperature annealed to accentuate ultrasonic response and provide dimensional stability 3
5.2 O3 — homogenized 3

6 Subdivisions of H temper designations **4**
6.1 General 4
6.2 First digit after H 4
6.3 Second digit after H 4
6.4 Third digit after H 5
6.5 Other digits after H 6

7 Subdivisions of T temper designations **6**
7.1 First digits (numerals 1 to 10) after T 6
7.2 Additional digits added to designations T1 to T10 8
7.3 Assigned additional digits for stress-relieved T tempers 8
7.3.1 Stress-relieved by stretching 8
7.3.2 Stress relieved by compressing 9
7.3.3 Stress relieved by combined stretching and compressing 9
7.4 Assigned additional digits for stress-relieved W tempers 9
7.5 Assigned additional digits for variations of T7 type tempers 9
7.6 Assigned additional digits for producer/supplier demonstration tempers and purchaser/user processed tempers 10
7.6.1 Temper designations for producer/supplier — Laboratory demonstration of response to heat treatment 10
7.6.2 Temper designations for producer/supplier — Demonstration of response to temper conversion 10
7.6.3 Temper designations for purchaser/user heat treatment 11

Annex A (informative) **Common, regionally applied temper designations and descriptions** **12**