

DIN EN 12168:2024-12 (E)

Copper and copper alloys - Hollow rod for free machining purposes

Contents		Page
	European foreword	4
	Introduction	6
1	Scope	7
2	Normative references	7
3	Terms and definitions	7
4	Designations	9
4.1	Material	9
4.1.1	General	9
4.1.2	Symbol	9
4.1.3	Number	9
4.2	Material condition	9
4.3	Product	9
5	Ordering information	12
6	Requirements	14
6.1	Composition	14
6.2	Mechanical properties	14
6.3	Resistance to dezincification	14
6.4	Residual stress level	14
6.5	Dimensions and tolerances	14
6.5.1	Diameter or width across-flats	14
6.5.2	Tolerance on wall thickness	14
6.5.3	Eccentricity	15
6.5.4	Shape tolerances	15
6.5.5	Straightness	15
6.5.6	Length	15
6.5.7	Corner radii	15
6.5.8	Twist of polygonal hollow rod	16
6.6	Surface quality	16
6.7	Internal inclusion	17
7	Sampling	17
7.1	General	17
7.2	Analysis	17
7.3	Mechanical tests	17
7.4	Dezincification resistance and stress corrosion resistance tests	17
8	Test methods	18
8.1	Analysis	18
8.2	Tensile test	18
8.2.1	General	18
8.2.2	Location of test pieces	18
8.2.3	Shape and size of test pieces	18
8.2.4	Procedure for testing	18
8.2.5	Determination of results	18
8.3	Hardness test	18

8.4	Dezincification resistance test	19
8.5	Stress corrosion resistance test	19
8.6	Retests	19
8.6.1	Analysis, tensile, hardness and dezincification resistance tests	19
8.6.2	Stress corrosion resistance test	19
8.7	Rounding of results	19
9	Certificate of Compliance and inspection documentation	20
9.1	Certificate of Compliance	20
9.2	Inspection documentation	20
10	Marking, packaging, labelling	20
Annex ZA (informative) Relationship between this European Standard and the essential requirements of Directive 2014/68/EU (Pressure equipment Directive) aimed to be covered		39
Bibliography		40