

DIN EN 15220-1:2011-07 (E)

Railway applications - Brake indicators - Part 1: Pneumatically operated brake indicators (includes Amendment A1:2011)

Contents		Page
Foreword		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	6
3.1	General	6
3.2	Components	7
3.3	Types of brake indicator	7
3.4	States	7
3.4.1	Service brake	7
3.4.2	Parking brake	7
3.8	Abbreviations	8
4	Requirements	8
4.1	Design and manufacturing	8
4.2	Operating conditions	9
4.3	Functional characteristics	9
4.3.1	General	9
4.3.2	Braking/release status	9
4.3.3	Lubrication	9
4.3.4	Leakage	9
4.4	Constructional characteristics	9
4.4.1	External appearance	9
4.4.2	Fire/smoke behaviour	10
4.4.3	Connections	10
4.4.4	Electric contacts	10
4.4.5	Space envelope	10
4.4.6	Indicator window	10
4.4.7	Brake indicator weight	11
4.4.8	Mechanical shock and vibration	11
4.4.9	Life expectancy	11
5	Type test methods	11
5.1	Sampling for type test	11
5.2	Test requirements	11
5.3	Test procedure	11
5.3.1	Principle	11
5.3.2	Check of physical and geometrical characteristics	12
5.3.3	Hydraulic test (water pressure) at given pressure	12
5.3.4	Protection against ingress of dust and water	13
5.3.5	Insulation test (brake indicators equipped with electrical contacts only)	14
5.3.6	Dielectric strength (brake indicators equipped with electrical contacts only)	14
5.3.7	Tightness test	15
5.3.8	Braking/release status control	17
5.3.9	Vibration test	19
5.3.10	Resistance to shock test	19
5.3.11	Endurance at ambient temperature test	19
5.3.12	Corrosion test	20
5.3.13	Fire/smoke behaviour	20

5.3.14	Examination	21
5.4	Approval validity	21
5.5	Type test report	21
6	Homologation testing	21
6.1	General	21
6.2	Service trial	21
6.3	Sample	22
6.4	Previous tests	22
6.5	Tests responsibility	22
6.5.1	Procedure	22
6.5.2	Pass/fail criteria	22
6.6	Homologation test report	22
7	Routine tests	22
8	Designation	23
9	Marking and packaging	23
9.1	Marking	23
9.2	Packing and protection	23
Annex A (informative) Brake indicator and parking brake indicator overall dimensions		24
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2008/57/EC of the European Parliament and of the Council of 17 June 2008 on the interoperability of the rail system within the Community (Recast)		29
Figures	Figure 1 -- Standard nozzle	14
	Figure 2 -- Air tightness equipment	15
	Figure 3 -- Tightness cycle test	16
	Figure 4 -- Tightness cycle test	16
	Figure 5 -- Braking/release status control equipment	18
	Figure 6 -- Braking/release cycle test	18
	Figure 7 -- Endurance cycle test	20
	Figure A.1 -- Single brake indicator and single parking brake indicator overall dimensions	24
	Figure A.2 -- Single brake indicator and single parking brake indicator with switch overall dimensions	25
	Figure A.3 -- Double brake indicator and double parking brake indicator overall dimensions	26
	Figure A.4 -- Single brake indicator and single parking brake indicator overall dimensions	27
	Figure A.5 -- Double brake indicator and double parking brake indicator overall dimensions with uncertain braking status indication	28
Tables	Table 1 -- Operations to be carried out for conformity assessment	12
	Table 2 -- Leakage permitted at test temperatures	16
	Table 3 -- Leakage permitted at test temperatures	17
	Table 4 -- Test programme	23

Table ZA.1 - Correspondence between this European Standard, the HS TSI RST published in the OJEU dated 26 March 2008 and Directive 2008/57/EC 30

Table ZA.2 - Correspondence between this European Standard, the CR TSI RST Freight Wagons dated July 2006, published in the OJEU on 8 December 2006 and its intermediate revision published in the OJEU on 14 February 2009 and Directive 2008/57/EC 31

Table ZA.3 - Correspondence between this European Standard, the CR LOC and PASS RST TSI (ST05EN05 dated 2010.06.10 accepted by RISC) and Directive 2008/57/EC 32