DIN EN 15220-1:2011-07 (E)

Railway applications - Brake indicators - Part 1: Pneumatically operated brake indicators (includes Amendment A1:2011)

Contents

Page

Foreword 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 6
3.1 General 6
3.2 Components 7
3.3 Types of brake indicator 7
3.4 States 7
3.4.1 Service brake 7
3.4.2 Parking brake 7
3.8 Abbreviations 8

4 Requirements 8
4.1 Design and manufacturing 8
4.2 Operating conditions 9
4.3 Functional characteristics 9
4.3.1 General 9
4.3.2 Braking/release status 9
4.3.3 Lubrication 9
4.3.4 Leakage 9
4.4 Constructional characteristics 9
4.4.1 External appearance 9
4.4.2 Fire/smoke behaviour 10
4.4.3 Connections 10
4.4.4 Electric contacts 10
4.4.5 Space envelope 10
4.4.6 Indicator window 10
4.4.7 Brake indicator weight 11
4.4.8 Mechanical shock and vibration 11
4.4.9 Life expectancy 11

5 Type test methods 11
5.1 Sampling for type test 11
5.2 Test requirements 11
5.3 Test procedure 11
5.3.1 Principle 11
5.3.2 Check of physical and geometrical characteristics 12
5.3.3 Hydraulic test (water pressure) at given pressure 12
5.3.4 Protection against ingress of dust and water 13
5.3.5 Insulation test (brake indicators equipped with electrical contacts only) 14
5.3.6 Dielectric strength (brake indicators equipped with electrical contacts only) 14
5.3.7 Tightness test 15
5.3.8 Braking/release status control 17
5.3.9 Vibration test 19
5.3.10 Resistance to shock test 19
5.3.11 Endurance at ambient temperature test 19
5.3.12 Corrosion test 20
5.3.13 Fire/smoke behaviour 20

5.3.14 Examination 21
5.4 Approval validity 21
5.5 Type test report 21

6 Homologation testing 21
6.1 General 21
6.2 Service trial 21
6.3 Sample 22
6.4 Previous tests 22
6.5 Tests responsibility 22
6.5.1 Procedure 22
6.5.2 Pass/fail criteria 22
6.6 Homologation test report 22

7 Routine tests 22

8 Designation 23

9 Marking and packaging 23
9.1 Marking 23
9.2 Packing and protection 23

Annex A (informative) Brake indicator and parking brake indicator overall dimensions 24

Annex ZA (informative) !!!!Relationship between this European Standard and the Essential Requirements of EU Directive 2008/57/EC of the European Parliament and of the Council of 17 June 2008 on the interoperability of the rail system within the Community (Recast)"""" 29

Figures Figure 1 -- Standard nozzle 14

Figure 2 -- Air tightness equipment 15

Figure 3 -- Tightness cycle test 16

Figure 4 -- Tightness cycle test 16

Figure 5 -- Braking/release status control equipment 18

Figure 6 -- Braking/release cycle test 18

Figure 7 -- Endurance cycle test 20

Figure A.1 -- Single brake indicator and single parking brake indicator overall dimensions 24

Figure A.2 -- Single brake indicator and single parking brake indicator with switch overall dimensions 25

Figure A.3 -- Double brake indicator and double parking brake indicator overall dimensions 26

Figure A.4 -- Single brake indicator and single parking brake indicator overall dimensions 27

Figure A.5 -- Double brake indicator and double parking brake indicator overall dimensions with uncertain braking status indication 28

Tables Table 1 -- Operations to be carried out for conformity assessment 12

Table 2 -- Leakage permitted at test temperatures 16

Table 3 -- Leakage permitted at test temperatures 17

Table 4 -- Test programme 23

Table ZA.1 - Correspondence between this European Standard, the HS TSI RST published in the OJEU dated 26 March 2008 and Directive 2008/57/EC 30

Table ZA.2 - Correspondence between this European Standard, the CR TSI RST Freight Wagons dated July 2006, published in the OJEU on 8 December 2006 and its intermediate revision published in the OJEU on 14 February 2009 and Directive 2008/57/EC 31

Table ZA.3 - Correspondence between this European Standard, the CR LOC and PASS RST TSI (ST05EN05 dated 2010.06.10 accepted by RISC) and Directive 2008/57/EC 32