

DIN EN 12561-2:2011-10 (E)

Railway applications - Tank wagons - Part 2: Bottom emptying devices for liquid products including vapour return

| Contents | | Page |
|---|---|-------------|
| Foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 4 |
| 4 | Requirements | 5 |
| 4.1 | General | 5 |
| 4.2 | Locks and seals | 5 |
| 4.3 | Dimensions | 5 |
| 5 | Bottom discharge line | 5 |
| 5.1 | General arrangement | 5 |
| 5.2 | Internal bottom valve | 6 |
| 5.3 | External valves | 6 |
| 5.4 | External branch pipes | 6 |
| 5.5 | Earthing devices | 6 |
| 6 | Vapour return line | 7 |
| 7 | Reserved spaces for connection devices | 7 |
| 8 | Threaded coupling | 9 |
| Annex A (informative) Quick couplings for vapour return | | 11 |
| Bibliography | | 12 |
| Figures Figure 1 -- General arrangement of bottom discharge line | | 6 |
| Figure 2 -- Example of vapour line arrangement | | 7 |
| Figure 3 -- Reserved spaces for connection devices | | 8 |
| Figure 4 -- Coupling dimensions | | 9 |
| Figure 5 -- Cap dimensions | | 10 |
| Figure A.1 -- Dimensions of vapour return coupling | | 11 |
| Table Table 1 -- Thread dimensions | | 9 |