

DIN EN 15273-3:2014-06 (E)

Railway applications - Gauges - Part 3: Structure gauges

Contents		Page
Foreword		7
Introduction		10
1	Scope	11
2	Normative references	12
3	Terms and definitions	12
4	Symbols, abbreviations and subscripts	15
4.1	Symbols and abbreviations	15
4.2	Subscripts	21
4.3	Notations	21
5	General information on all the gauging methods	22
5.1	The reference profile and its associated rules	22
5.2	Transverse widening	22
5.2.1	Gauge variations depending on the local situation	22
5.2.2	Random transverse phenomena	23
5.3	Superelevation and lowering perpendicular to the running surface	24
5.3.1	General	24
5.3.2	Vertical superelevation or lowering for longitudinal profile transition curves	24
5.3.3	Vertical effect of the roll	25
5.3.4	Uplift	27
5.3.5	Vertical random phenomena	27
5.4	Additional allowances	27
5.5	Gauge types	27
5.5.1	Gauge methodologies	27
5.5.2	Structure gauge types	28
5.5.3	Uniform gauge	28
5.6	Choice of gauge	29
5.6.1	Gauge and methodology choice	29
5.6.2	Structure gauge choice	29
5.6.3	Taking account of the allowances	30
5.6.4	Catalogue of gauges	30
6	Rules for determination of the static gauge	30
6.1	General	30
6.2	Associated rules	31
6.3	Transverse clearances	32
6.3.1	Phenomena considered	32
6.3.2	Determination of the sum of allowances j	32
6.4	Vertical allowances for random phenomena	33
6.4.1	Phenomena considered	33
6.4.2	Determination of the sum of vertical allowances V	33
7	Rules for determination of the kinematic gauge	34
7.1	General	34
7.2	Associated rules	34
7.3	Transverse allowances for random phenomena	35
7.3.1	Phenomena considered	35

7.3.2	Determination of the sum of transverse allowances j	35
7.4	Vertical allowances for random phenomena	36
7.4.1	Phenomena considered	36
7.4.2	Determination of the sum of vertical allowances V	36
8	Rules for determination of the dynamic gauge	37
8.1	General	37
8.2	Associated rules	37
8.3	Transverse allowances for random phenomena	38
8.3.1	Phenomena considered	38
8.3.2	Determination of the sum of allowances j	38
8.4	Vertical allowances for random phenomena	39
8.4.1	Phenomena considered	39
8.4.2	Determination of the sum of vertical allowances V	39
9	Distance between track centres	39
9.1	General	39
9.2	Determination of the limit distance between track centres	40
9.2.1	General	40
9.2.2	Effect of cant difference bD	41
9.2.3	Allowances to take into account random phenomena	42
9.2.4	Determination	43
9.3	Determination of the nominal distance between track centres	44
9.3.1	General	44
9.3.2	Determination	44
10	Elements of variable layout	45
10.1	General	45
10.1.1	Calculation principle	45
10.1.2	Characteristics of a layout transition	45
10.1.3	Gauge variations	46
10.2	Layout transition	46
10.2.1	Sudden change of curvature	46
10.2.2	Smooth transition of curvature	47
10.3	Crossing of a switch or crossing	48
10.3.1	General	48
10.3.2	Additional overthrow variations	49
10.3.3	Quasi-static effect variations	50
10.3.4	Result	50
11	Determination of the pantograph free passage gauge	50
11.1	General	50
11.1.1	Space to be cleared for electrified lines	50
11.1.2	Particularities	51
11.1.3	Basic principles	51
11.2	Determination of the pantograph free passage mechanical gauge (in the case of the kinematic gauge)	52
11.2.1	Determination of the mechanical gauge width	52
11.2.2	Determination of the maximum height heff of the mechanical gauge	54
11.3	Pantograph electrical gauge (in the case of the kinematic gauge)	55
11.3.1	General	55
11.3.2	Pantograph electrical gauge width	55
11.3.3	Electrical gauge height	56
11.3.4	Insulating distance	56
11.4	Determination of the pantograph gauge in the case of the dynamic gauge	56
12	Overhead contact wire	56
13	Rules for installation of platform edges	57
13.1	General	57
13.2	Gap blac 0 and hlac 0	60
13.3	Installation dimensions	61

13.3.1	Installation relative to the running surface	61
13.3.2	Installation relative to the horizontal (xq, yq)	62
13.3.3	Installation tolerances	62
13.4	Verification and tolerances	62
14	Tilting trains	62
14.1	General	62
14.2	Transition curve	64
14.3	Degraded modes	64
15	Rules for ferries	64
16	Track accessories	65
16.1	General	65
16.2	Contact ramps	65
16.3	Active check rails	65
16.4	Planking of level crossings	65
16.5	Electric third rail	65
16.6	Rail brakes	66
17	Verification and maintenance of the gauge	66
17.1	Structure gauges	66
17.2	Distance between track centres	66
18	Guide for determination of a new gauge from an existing infrastructure	67
Annex A (normative) Calculation methodology for structure gauge allowances		68
A.1	General	68
A.2	Formulation in the case of the kinematic gauge	68
A.2.1	For the installation nominal gauge	68
A.2.2	For the installation limit gauge	69
A.2.3	For the verification limit gauge	70
A.2.4	For the installation nominal distance between centres	71
A.2.5	For the installation limit distance between centres	72
A.2.6	For the verification limit distance between centres	72
A.2.7	For the pantograph gauge	72
A.3	Formulation in the case of the dynamic gauge	72
A.3.1	General	72
A.3.2	For the installation nominal gauge	73
A.3.3	For the installation limit gauge	73
A.3.4	For the verification limit gauge	74
A.3.5	For the nominal installation distance between centres	75
A.3.6	For the verification limit distance between centres	75
A.3.7	For the pantograph gauge	76
Annex B (informative) Recommended values for calculation of the structure gauge and calculation examples		77
B.1	Recommendations for coefficients	77
B.2	Examples of kinematic calculation	78
B.2.1	Verification limit gauge, installation limit gauge and installation nominal gauge	78
B.2.2	Nominal, installation limit and verification limit distances between centres	80
B.2.3	Pantograph gauge	81
Annex C (normative) International gauges G1, GA, GB and GC, GI1, GI2 and GI3		88
C.1	General	88
C.1.1	Application	88
C.1.2	Gauge types	88
C.1.3	Parameters and common rules	88
C.1.4	Calculation of distance between centres	89

C.1.5	Pantograph free passage gauge	89
C.1.6	Gauge parts	89
C.2	Gauge for the upper parts (h > 400 mm)	90
C.2.1	Gauge G1	90
C.2.2	Gauges GA and GB	91
C.2.3	Gauge GC	93
C.3	Lower parts (h 0,400 m)	94
C.3.1	Lower parts of GI2 - generally applicable	94
C.3.2	Lower parts of GI1 - Tracks for rail brake equipment	95
C.3.3	Lower parts for "rolling" roads - GI3	100
C.4	Pantograph free passage gauge	102
Annex D (normative) Gauges for multilateral and national agreements		103
D.1	General	103
D.2	Kinematic gauges derived from international gauges	103
D.2.1	Gauge G2	103
D.2.2	Gauges GB1 and GB2	105
D.3	Static gauges derived from international gauges	107
D.3.1	Gauge G1	107
D.3.2	Gauge G2	111
D.3.3	Gauges GA, GB and GC	112
D.4	National application gauge	114
D.4.1	Belgian gauges BE1, BE2 and BE3	114
D.4.2	French gauges FR-3.3	118
D.4.3	Portuguese gauges PTb, PTb+ and PTc	120
D.4.4	Finnish gauge FIN1	126
D.4.5	Swedish gauges SEa and SEc	129
D.4.6	German gauge DE1	132
D.4.7	German gauge DE2	134
D.4.8	German gauge DE3	135
D.4.9	Czech gauge Z-GCD	137
D.4.10	British gauge	138
D.4.11	Spanish gauges GHE16, GEA16, GEB16, GEC16, GEC14, GEE10 and GED10	139
Annex E (informative) Calculation example for determination of the gauge at a switch or crossing		155
E.1	General	155
E.2	Methodology	156
E.3	Widening in the curve	156
E.3.1	Widening of the main line	156
E.3.2	Widening in the turnout route	158
E.4	The quasi-static effect	159
E.5	Gauge widening at a switch or crossing	160
Annex F (normative) Determination of reference vehicle characteristics		163
F.1	General	163
F.2	Methodology	163
F.3	Calculation example	164
F.3.1	General	164
F.3.2	Vehicle no. 1 (on the inside of the curve)	164
F.3.3	Vehicle no. 2 (on the outside of the curve)	164
F.3.4	Vehicle no. 3 (on the inside of the curve)	165
F.3.5	Vehicle no. 4 (on the outside of the curve)	165
F.3.6	Summary	165
F.3.7	International gauge reference vehicles	166
Annex G (normative) Uniform gauge		168
G.1	General	168
G.2	GU1	168

G.2.1	General	168
G.2.2	Determination of the gauge	168
G.2.3	Equivalent kinematic gauge	170
G.3	GU2	170
G.3.1	General	170
G.3.2	Determination of the gauge	171
G.4	GUC	172
G.4.1	General	172
G.4.2	Determination of the gauge	173
Annex H (informative) Gauge maintenance guideline		174
H.1	General	174
H.2	Choice of gauge	174
H.3	Installation rules	174
H.3.1	Guidelines for installation of equipment along the track	174
H.3.2	Guidelines for the installation of tracks alongside structures	174
H.3.3	Guidelines for the installation of temporary structures	175
H.4	Managing and checking of structures	175
H.4.1	Management principles	175
H.4.2	Management of critical situations	175
H.4.3	Practical aspects for measuring the structures	176
H.5	Effect of track maintenance	176
H.6	Personnel training	176
Annex I (informative) A-deviations		177
Annexe ZA (informative) Relationship between this European Standard and the essential requirements of EU Directive 2008/57/EC		179
Bibliography		184