DIN EN 16272-6:2014-12 (E)

Railway applications - Track - Noise barriers and related devices acting on airborne sound propagation - Test method for determining the acoustic performance - Part 6: Intrinsic characteristics - In situ values of airborne sound insulation under direct sound field conditions

Contents

Page

Foreword 4

Introduction 5

1 Scope 8

2 Normative references 8

3 Terms and definitions 8

4 Symbols and abbreviations 13

5 Sound insulation index measurements 15
5.1 General principle 15
5.2 Measured quantity 15
5.3 Test arrangement 16
5.4 Measuring equipment 20
5.4.1 Components of the measuring system 20
5.4.2 Sound source 21
5.4.3 Test signal 21
5.5 Data processing 21
5.5.1 Calibration 21
5.5.2 Sample rate 22
5.5.3 Background noise 22
5.5.4 Scanning technique using a single microphone 22
5.5.5 Scanning technique using nine microphones 23
5.5.6 Adrienne temporal window 23
5.5.7 Placement of the Adrienne temporal window 24
5.5.8 Low frequency limit and sample size 25
5.6 Positioning of the measuring equipment 26
5.6.1 Selection of the measurement positions 26
5.6.2 Post measurements 27
5.6.3 Additional measurements 27
5.6.4 Reflecting objects 27
5.6.5 Safety considerations 27
5.7 Sample surface and meteorological conditions 28
5.7.1 Condition of the sample surface 28
5.7.2 Wind 28
5.7.3 Air temperature 28

6 Measurement uncertainty 28

7 Measuring procedure 28

8 Test report 29
8.1 Expression of results 29
8.2 Further information 29

Annex A (informative) Measurement uncertainty 31

A.1 General 31
A.2 Expression for the calculation of sound insulation index 31
A.3 Contributions to measurement uncertainty 32
A.4 Expanded uncertainty of measurement 33
A.5 Measurement uncertainty based upon reproducibility data 33

Annex B (informative) Template of test report on airborne sound insulation of railway noise barriers 34

B.1 Template of test report 34
B.2 Test setup (example) 36
B.3 Test object and test situation (example) 38
B.4 Results (example) 40

Bibliography 46