

DIN EN 15273-2:2014-09 (E)

Railway applications - Gauges - Part 2: Rolling stock gauge

| Contents | | Page |
|-------------------------------------|--------------------------------------------------------------------------------------------|-------------|
| Foreword | | 8 |
| Introduction | | 15 |
| 1 | Scope | 16 |
| 2 | Normative references | 16 |
| 3 | Terms and definitions | 16 |
| 4 | Symbols | 17 |
| 5 | Common requirements | 24 |
| 5.1 | Static and kinematic gauges | 24 |
| 5.1.1 | Description of the calculation method | 24 |
| 5.1.2 | Vehicle classes | 24 |
| 5.1.3 | Applicability of static and kinematic gauges depending on running gear of the vehicle ... | 25 |
| 5.1.4 | Limitations for the use of static gauges | 26 |
| 5.1.5 | Requirements for use of kinematic gauges | 26 |
| 5.1.6 | Dimensional tolerances on vehicles | 27 |
| 5.2 | Dynamic methods | 27 |
| 5.2.1 | General principles | 27 |
| 5.2.2 | Dynamic method based on a reference profile | 27 |
| Annexe A (normative) Gauge G1 | | 29 |
| A.1 | General | 29 |
| A.1.1 | Bogie classes | 29 |
| A.1.2 | Rail-wheel adhesion coefficient | 29 |
| A.1.3 | Minimum horizontal curve radius | 29 |
| A.2 | Static gauge G1 | 30 |
| A.2.1 | Reference profiles for the lateral parts and upper parts | 30 |
| A.2.2 | Reference profiles of the lower part of static gauge G1 | 31 |
| A.2.3 | Associated rules for static gauge G1 | 32 |
| A.2.4 | Reduction formulae | 33 |
| A.3 | Kinematic gauge G1 | 34 |
| A.3.1 | General | 34 |
| A.3.2 | Reference profiles of the upperparts of gauge G1 | 35 |
| A.3.3 | Reference profiles of the lower part of kinematic gauge G1 | 35 |
| A.3.4 | Determination of the vehicle heights | 38 |
| A.3.5 | Contact ramps | 51 |
| A.3.6 | Use of shunting devices on curved tracks | 53 |
| A.3.7 | Conditions for embarkation onto ferries | 54 |
| A.3.8 | Taking account of the transverse displacements of vehicles | 55 |
| A.3.9 | Formulae | 56 |
| A.3.10 | Reduction formulae applicable to wagons (dimensions in metres) | 63 |
| A.3.11 | Formulae to be applied for bogies and associated parts | 64 |
| A.3.12 | Verification of gauge of pantographs and non-insulated live parts on vehicle roof | 65 |
| A.3.13 | Pantograph gauge verification for tilting body vehicles or running with IP > IC | 70 |
| A.3.14 | Specific rules for doors in the open position and movable steps in the exit position | 74 |
| A.3.15 | Position of steps | 74 |
| A.3.16 | Tilting vehicles | 75 |

| | | |
|------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-----|
| A.4 | Track operation position of the vehicles: angular displacement coefficient (A) | 84 |
| Annexe B (normative) Gauges GA, GB, GC | | 89 |
| B.1 | Common elements with gauge G1 | 89 |
| B.2 | Static gauges GA, GB, and GC (loading gauges) | 89 |
| B.2.1 | Upper part reference profiles | 90 |
| B.2.2 | Reduction calculation formulae for static gauges GA and GB | 90 |
| B.2.3 | Reduction calculation formulae for static gauges GC | 91 |
| B.3 | Kinematic gauges GA, GB, and GC | 91 |
| B.3.1 | Upper part reference profiles | 92 |
| B.3.2 | Reference profiles for lower parts | 92 |
| B.3.3 | Formulae for traction units (except motor coaches) | 92 |
| B.3.4 | Formulae for motor coaches | 95 |
| B.3.5 | Formulae for coaches and vans | 97 |
| B.3.6 | Formulae for wagons | 99 |
| Annexe C (normative) Gauges GB1, GB2 | | 102 |
| C.1 | Static gauges GB1 and GB2 | 102 |
| C.1.1 | Reference profile of static gauge GB1 | 102 |
| C.1.2 | Kinematic gauges GB1 and GB2 | 104 |
| Annexe D (normative) Kinematic gauge GI3 | | 106 |
| D.1 | Reference profile GI3 | 106 |
| D.2 | Associated rules for the kinematic reference profile to determine the maximum vehicle profile | 107 |
| D.2.1 | Traction units (except motor coaches) | 107 |
| D.2.2 | Motor coaches | 109 |
| D.2.3 | Coaches and vans | 110 |
| D.2.4 | Wagons | 112 |
| Annexe E (normative) Gauge G2 | | 115 |
| E.1 | Static gauge G2 | 115 |
| E.1.1 | Reference profile for static gauge G2 | 115 |
| E.1.2 | Reference profile of kinematic gauge G2 | 116 |
| Annexe F (normative) Finnish gauge FIN1 | | 117 |
| F.1 | General | 117 |
| F.2 | Associated rules | 117 |
| F.2.1 | Vertical position of the vehicle | 117 |
| F.2.2 | Lower parts of the rolling stock | 117 |
| F.2.3 | Rolling stock parts close to the wheel flanges | 117 |
| F.2.4 | Rolling stock width | 118 |
| F.2.5 | Movable steps and access doors opening outwards for coaches and motor coaches | 118 |
| F.2.6 | Pantographs and non-insulated roof-mounted parts | 118 |
| F.2.7 | Rules and instructions | 118 |
| F.3 | Reduction formulae | 118 |
| F.3.1 | General rules | 118 |
| F.3.2 | Reduction formulae | 119 |
| F.4 | Reference profiles of gauge FIN1 | 120 |
| F.5 | Increase in the minimum height of the lower part of the rolling stock able to pass over marshalling humps and rail brakes | 121 |
| F.6 | Increase in the minimum height of the lower part of the rolling stock unable to pass over marshalling humps and rail brakes | 121 |
| F.7 | Passage over transitions and humps | 122 |
| F.7.1 | Position of rail brakes and other shunting devices | 122 |
| F.7.2 | Running over marshalling hump passing track | 123 |
| F.8 | Gauge of the vehicle lower step | 123 |

| | | |
|--------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| F.8.1 | General | 123 |
| F.8.2 | Requirements for the distance between the step and the platform in the transverse plane | 124 |
| F.8.3 | Gauge check | 124 |
| F.9 | Gauge of outwards opening doors and of folded down steps for coaches and motor coaches | 124 |
| F.9.1 | General | 124 |
| F.9.2 | Requirements for the distance between the door and the fixed equipment in the transverse plane | 125 |
| F.9.3 | Gauge check | 125 |
| F.10 | Pantographs and non-insulated parts | 126 |
| Annexe G (normative) French gauge FR 3.3 | | 127 |
| G.1 | General | 127 |
| G.2 | Reference profile of kinematic gauge FR 3.3 | 128 |
| G.3 | Reference kinematic profiles for lower parts | 128 |
| G.4 | Associated rules for kinematic gauge FR 3.3 for determining the kinematic gauge | 128 |
| G.4.1 | Vertical reductions | 128 |
| G.4.2 | Transversal reductions for heights $h > 3,250$ m | 129 |
| G.4.3 | Verification of gauge of pantographs and non-insulated live parts on vehicle roof | 134 |
| Annexe H (normative) Belgian gauges BE1, BE2 and BE3 | | 135 |
| H.1 | General | 135 |
| H.2 | Associated rules | 135 |
| H.2.1 | Rules for the lower parts | 135 |
| H.2.2 | Upwards vertical displacements | 135 |
| H.2.3 | Side doors in the open position | 136 |
| H.2.4 | Movable step rules | 136 |
| H.2.5 | Pantograph rules | 136 |
| H.3 | Kinematic reference profiles for the upper parts | 137 |
| H.4 | Reduction formulae | 139 |
| H.4.1 | Reduction formulae for traction units | 139 |
| H.4.2 | Reduction formulae for hauled vehicles | 142 |
| H.5 | Kinematic gauge of the 3 kV and 25 kV pantograph in the collection position on the Belgian network | 145 |
| H.5.1 | General principles | 145 |
| H.5.2 | Verification of pantographs located between the end wheelsets or between the bogie centres (verification of stationary vehicle on a canted track) | 145 |
| H.5.3 | Verification of pantographs located beyond the end wheelsets or beyond the bogie centres (verification in operation on an insufficiently canted track) | 146 |
| H.5.4 | Pantographs in the lowered position | 146 |
| H.5.5 | Other non-insulated roof-mounted parts | 146 |
| Annexe I (normative) Portuguese gauges PTb, PTb+, PTc | | 148 |
| I.1 | General | 148 |
| I.2 | Kinematic reference profiles | 149 |
| I.3 | Reference profiles for the lower part | 152 |
| I.4 | Associated rules for PT gauges | 153 |
| I.4.1 | Vertical displacements | 153 |
| I.4.2 | Transverse displacements | 153 |
| I.4.3 | Associated rules for the parts of height $h < 400$ mm above the running surface | 153 |
| I.4.4 | Reduction formulae | 154 |
| I.5 | Associated rules for pantographs and other roof-mounted parts | 158 |
| I.5.1 | Reference profile for pantographs | 158 |
| I.5.2 | Pantograph in collecting position | 159 |
| I.5.3 | Pantograph in the lowered position and other roof-mounted parts | 160 |
| I.6 | Associated rules for tilting body vehicles | 160 |
| I.6.1 | Quasi-static displacements (z_p) | 160 |
| I.6.2 | Calculation of the reductions | 161 |

| | | |
|--------------------------------------------------------|--------------------------------------------------------------------------------------------|-----|
| I.6.3 | Requirement for adjusting the tilting system for vehicles fitted with active systems | 162 |
| I.6.4 | Limits related to the speed of tilting body vehicles | 163 |
| Annexe J (normative) Swedish gauges SEa and SEc | | 164 |
| J.1 | Swedish dynamic gauges SEa and SEc: General | 164 |
| J.2 | Reference profiles | 165 |
| J.3 | Reference profile of gauge SEa | 165 |
| J.4 | Reference profile for lower part of gauges SEa and SEc | 166 |
| J.5 | Pantograph reference profile for gauge SEa | 166 |
| J.6 | Dynamic reference profile SEc | 167 |
| J.6.1 | Reference profile for parts below 0,15 m of gauge SEc | 167 |
| J.6.2 | Reference profile for pantograph for gauge SEc | 168 |
| J.7 | Methodology for calculating movements by means of geometric formulae | 168 |
| J.7.1 | Curves in the horizontal plane | 169 |
| J.7.2 | Straight track | 171 |
| J.7.3 | Vertical curves, calculation of upper parts | 172 |
| J.7.4 | Calculation of the lower parts | 173 |
| J.7.5 | Marshalling humps | 174 |
| J.7.6 | Ferry ramps | 174 |
| J.7.7 | Pantograph | 175 |
| J.7.8 | Swept envelope | 175 |
| J.8 | Methodology for calculating movements by simulation | 176 |
| J.8.1 | Modelling and simulations | 178 |
| J.8.2 | Parameters to be considered in the simulations | 178 |
| J.8.3 | Cases of simulation | 179 |
| J.8.4 | Horizontal curves | 179 |
| J.8.5 | Straight track | 179 |
| J.8.6 | Running over points | 180 |
| J.8.7 | Track parameters | 180 |
| J.8.8 | Calculation parameters | 180 |
| J.8.9 | Statistical post-processing | 181 |
| J.8.10 | Geometric overthrow in a horizontal curve | 181 |
| J.8.11 | Vertical geometric movement towards the upper part of the profile | 182 |
| J.8.12 | Vertical geometric movement towards the lower part of the profile | 182 |
| J.8.13 | Marshalling humps | 183 |
| J.8.14 | Ferry ramps | 184 |
| J.8.15 | Pantographs | 184 |
| J.8.16 | Swept envelope | 185 |
| J.9 | Checking relative to the permitted reference profile | 185 |
| J.10 | Dynamic gauging method: verification | 185 |
| J.10.1 | Verification by simulation | 186 |
| J.10.2 | Verification by static testing | 186 |
| J.10.3 | Verification by on-line running tests | 187 |
| J.10.4 | (Informative) Dynamic gauge: Irregularities | 187 |
| J.11 | (Informative) Two-dimensional statistical post processing | 188 |
| J.12 | (Informative) Input data catalogue | 189 |
| Annexe K (normative) Static gauges OSJD | | 191 |
| K.1 | Static reference profiles of the upper parts (for rolling stock) | 191 |
| K.2 | Associated rules | 193 |
| K.2.1 | Additional overthrows for h 3,220 m | 193 |
| K.2.2 | Reduction formulae | 193 |
| K.3 | Determination of the allowable vertical dimensions | 195 |
| K.4 | Static reference profiles for the lower parts | 196 |
| Annexe L (normative) German gauges DE1, DE2, DE3 | | 198 |
| L.1 | Gauge DE1 | 198 |
| L.1.1 | Kinematic reference profile | 198 |
| L.1.2 | Associated rules | 199 |

| | | |
|------------------------------------------------------------------------------|----------------------------------------------------------|------------|
| L.2 | Kinematic gauge DE2 | 200 |
| L.2.1 | Kinematic reference profile | 200 |
| L.2.2 | Associated rules | 201 |
| L.3 | Kinematic gauge DE3 | 202 |
| L.3.1 | Kinematic reference profile | 202 |
| L.3.2 | Associated rules | 202 |
| L.4 | Absolute gauging of pantographs | 203 |
| L.4.1 | General | 203 |
| L.4.2 | Associated rules | 203 |
| L.4.3 | Contact wire | 205 |
| L.4.4 | Responsibility for input data | 205 |
| Annexe M (normative) Netherlands gauges NL1 and NL2 | | 208 |
| M.1 | Reference profiles of kinematic gauges NL1 and NL2 | 208 |
| M.2 | Associated rules | 209 |
| Annexe N (informative) UK gauging methods | | 210 |
| N.1 | General | 210 |
| N.1.1 | Gauge types | 210 |
| N.1.2 | Maintenance | 210 |
| N.1.3 | Tolerances | 210 |
| N.1.4 | Multiple operation | 210 |
| N.1.5 | Configuration | 210 |
| N.1.6 | Reference axes | 211 |
| N.1.7 | Vehicle data | 211 |
| N.2 | Static gauging | 211 |
| N.2.1 | Principles | 211 |
| N.2.2 | Vehicle geometry | 212 |
| N.2.3 | Suspension displacements | 213 |
| N.3 | Dynamic gauging | 214 |
| N.3.1 | Principles | 214 |
| N.3.2 | Geometric gauging | 214 |
| N.3.3 | Absolute gauging | 216 |
| N.3.4 | Comparative gauging | 218 |
| N.3.5 | Vehicle shape and size | 221 |
| N.3.6 | Range of operating conditions | 222 |
| N.3.7 | Suspension movements | 225 |
| N.3.8 | Calculating swept envelopes | 225 |
| N.3.9 | Dynamic reference profiles | 232 |
| N.3.10 | Assessing the vehicle | 235 |
| N.4 | UK geometric gauges | 236 |
| Annexe O (informative) Recommended practice for dynamic gauging | | 237 |
| O.1 | Vehicle models | 237 |
| O.1.1 | Principles | 237 |
| O.1.2 | Vehicle conditions | 237 |
| O.1.3 | Masses | 237 |
| O.1.4 | Suspension modelling | 238 |
| O.1.5 | Stiffness | 238 |
| O.1.6 | Dampers | 238 |
| O.1.7 | Air springs | 238 |
| O.1.8 | Swing links | 239 |
| O.1.9 | Friction | 239 |
| O.1.10 | Active devices | 239 |
| O.1.11 | Inter-vehicle connections | 239 |
| O.1.12 | Suspension component tolerances | 240 |
| O.1.13 | Suspension maintenance allowances | 240 |
| O.1.14 | Suspension failure modes | 240 |
| O.1.15 | Vehicle modelling accuracy | 240 |

| | | |
|-------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|------------|
| O.2 | Validation of vehicle modelling | 240 |
| O.2.1 | General notes on validation tests | 240 |
| O.2.2 | Simulation model | 242 |
| O.2.3 | Matching accuracy | 243 |
| O.2.4 | Weighbridge test | 243 |
| O.2.5 | Bogie rotation test | 244 |
| O.2.6 | Sway test | 244 |
| O.2.7 | Dynamic ride test | 245 |
| O.3 | Simulation method | 246 |
| O.3.1 | Principles | 246 |
| O.3.2 | Dynamic analysis | 246 |
| O.3.3 | Track data | 247 |
| O.3.4 | Cant, speed and curve radius: general cases | 247 |
| O.3.5 | Cant, speed and curve radius: specific cases | 248 |
| O.3.6 | Application of cant and curve radius | 248 |
| O.3.7 | Side wind loads | 248 |
| O.3.8 | Transient outputs | 248 |
| O.3.9 | Curving analysis | 251 |
| O.4 | Example of a virtual route | 252 |
| O.5 | Example of a drawing showing vehicle size and shape | 255 |
| O.6 | Presentation of swept envelope data | 256 |
| O.6.1 | Presentation of results | 256 |
| O.6.2 | Heading format | 256 |
| O.6.3 | Transient results matrix | 257 |
| O.6.4 | Curving results matrix | 258 |
| Annexe P (normative) Spanish gauges GHE16, GEA16, GEB16, GEC16, GEC14, GEE10 and GED10 | | 259 |
| P.1 | General | 259 |
| P.2 | Static gauges GHE16, GEA16, GEB16, GEC16, GEE10 and GED10 | 260 |
| P.2.1 | Reference profiles for static gauges | 260 |
| P.2.2 | Associated rules | 268 |
| P.3 | Kinematic gauges GHE16, GEA16, GEB16, GEC16, GEC14, GEE10 and GED10 | 271 |
| P.3.1 | Reference profiles for kinematic gauges | 271 |
| P.3.2 | Associated rules | 280 |
| Annexe Q (normative) Vehicle widening depending on the available spaces of the infrastructure .. | | 298 |
| Annexe R (normative) Static and kinematic gauges: list of documents for a vehicle gauge conformance certification | | 299 |
| R.1 | General | 299 |
| R.2 | List of documents to be produced for design control | 299 |
| R.3 | List of documents to be taken into account to verify conformity to the gauge | 299 |
| Annexe S (informative) A-deviations | | 301 |
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2008/57/EC | | 303 |
| Bibliography | | 309 |