

# DIN EN 16273:2015-03 (E)

## Railway applications - Track - Forged rail transitions

---

<b>Contents</b>		<b>Page</b>
Foreword .....		4
Introduction .....		5
1	Scope .....	6
2	Normative references .....	6
3	Terms and definitions .....	6
4	Information to be supplied for approval .....	8
4.1	By the purchaser .....	8
4.2	By the manufacturer .....	8
5	Approval of the manufacturer .....	8
6	Requirements for the forging process .....	9
6.1	General .....	9
6.2	Forging parameters .....	9
6.3	Post heat treatment .....	9
6.4	Profile finishing .....	9
6.5	Cutting to length .....	9
6.6	Identification .....	9
7	Procedure approval .....	9
7.1	General .....	9
7.2	Test specimen preparation .....	10
7.3	Number of specimens .....	10
7.4	Non-destructive approval tests .....	10
7.4.1	Geometry and dimensions .....	10
7.4.2	Visual inspection .....	13
7.4.3	Surface finish .....	13
7.4.4	Dye penetrant (DPI) or magnetic particle inspection (MPI) .....	13
7.4.5	Ultrasonic testing (UT) .....	13
7.5	Destructive approval tests .....	14
7.5.1	Hardness distribution .....	14
7.5.2	Switch rails: hardness distribution in the rail head .....	16
7.6	Test report .....	18
7.7	Validity of approval .....	18
8	Production tests .....	18
8.1	Switches .....	18
8.1.1	General .....	18
8.1.2	Geometry and dimensions .....	19
8.1.3	Hardness testing .....	19
8.2	Transition rails .....	20
8.2.1	General .....	20
8.2.2	Hardness .....	20
Annex A (informative)	Ultrasonic testing .....	22
A.1	Reference line (DAC) generation - reference block .....	22

<b>A.2</b>	<b>Reference line (DAC) generation and acceptance criteria .....</b>	<b>23</b>
	<b>Annex B (informative) Documentation of approval tests .....</b>	<b>24</b>
<b>B.1</b>	<b>Forged switch rails .....</b>	<b>24</b>
<b>B.1.1</b>	<b>General information .....</b>	<b>24</b>
<b>B.1.2</b>	<b>Geometry and dimensions .....</b>	<b>24</b>
<b>B.1.3</b>	<b>Dye penetrant (DPI) or magnetic particle inspection (MPI) .....</b>	<b>27</b>
<b>B.1.4</b>	<b>Ultrasonic testing (UT) .....</b>	<b>27</b>
<b>B.1.5</b>	<b>Hardness distribution on the surface .....</b>	<b>28</b>
<b>B.1.6</b>	<b>Test results of hardness distribution on the rail head .....</b>	<b>28</b>
<b>B.1.7</b>	<b>Test results of hardness distribution on the rail foot .....</b>	<b>30</b>
<b>B.2</b>	<b>Forged transition rails .....</b>	<b>32</b>
<b>B.2.1</b>	<b>General information .....</b>	<b>32</b>
<b>B.2.2</b>	<b>Geometry and dimensions .....</b>	<b>33</b>
<b>B.2.3</b>	<b>Dye penetrant (DPI) or magnetic particle inspection (MPI) .....</b>	<b>34</b>
<b>B.2.4</b>	<b>Ultrasonic testing (UT) .....</b>	<b>34</b>
<b>B.2.5</b>	<b>Hardness distribution on the surface .....</b>	<b>35</b>
<b>B.2.6</b>	<b>Test results of hardness distribution on the rail head .....</b>	<b>36</b>
<b>B.2.7</b>	<b>Test results of hardness distribution on the rail foot .....</b>	<b>36</b>
	<b>Bibliography .....</b>	<b>38</b>