

DIN EN 15313:2016-09 (E)

Railway applications - In-service wheelset operation requirements - In-service and off-vehicle wheelset maintenance

| Contents | | Page |
|-------------------------|--|-------------|
| European foreword | | 6 |
| Introduction | | 7 |
| 1 | Scope | 8 |
| 2 | Normative references | 9 |
| 3 | Terms and definitions | 9 |
| 4 | Maintenance | 10 |
| 4.1 | General | 10 |
| 4.2 | Maintenance organization | 11 |
| 4.2.1 | Maintenance organization plan | 11 |
| 4.2.2 | Maintenance plan | 11 |
| 4.2.3 | Service experience | 12 |
| 4.2.4 | Traceability - storage - transportation | 12 |
| 4.3 | Equipment and systems | 14 |
| 4.4 | Staff certification and competence | 14 |
| 4.5 | Qualification of an undertaking for the maintenance of in-service or off-vehicle wheelsets | 14 |
| 5 | Definition and illustrations of a boxed wheelset, its associated components and defects . | 16 |
| 5.1 | Definition and illustrations of a wheelset | 16 |
| 5.1.1 | Wheelset | 16 |
| 5.1.2 | Axle | 18 |
| 5.1.3 | Wheel | 19 |
| 5.1.4 | Axle box | 21 |
| 5.2 | Functional references of the rail-wheel interface | 21 |
| 5.2.1 | Wheelset functional references | 21 |
| 5.2.2 | Wheel functional references | 22 |
| 5.3 | Definition and illustrations of defects | 23 |
| 6 | Requirements and operations | 23 |
| 6.1 | General | 23 |
| 6.2 | Requirements | 24 |
| 6.2.1 | In-service limit dimensions and positions | 24 |
| 6.2.2 | Special maintenance action for freight wagon axles according to axle load | 27 |
| 6.2.3 | Maintenance decision criteria for in-service wheels for all types of wheel | 28 |
| 6.2.4 | Maintenance decision criteria for in-service wheels for specific wheel types | 31 |
| 6.2.5 | Damage acceptance limits for axle bodies | 31 |
| 6.2.6 | Criteria for axle box (Annex C.5) | 32 |
| 6.2.7 | Criteria on boxed wheelsets | 32 |
| 6.2.8 | Specific requirements for tyred wheels and resilient wheels | 33 |
| 6.2.9 | Limit value for axle wheel seat diameter | 34 |
| 6.3 | Reprofiling operation | 34 |
| 6.4 | Dimensions and conditions after reprofiling or an operation on the rim | 35 |
| 6.4.1 | Front-to-front dimension "a2" | 35 |
| 6.4.2 | Diameter difference between wheels on the same axle | 35 |
| 6.4.3 | Limit values of radial run-out as a function of the maximum operating speed authorized for the vehicle | 35 |

| | | |
|--------|--|----|
| 6.4.4 | Wheel axial run-out as a function of the maximum operating speed authorized for the vehicle | 35 |
| 6.4.5 | Parts of the tread that are not re-profiled | 35 |
| 6.4.6 | Radial traces and radial defects on the internal side of the rim | 36 |
| 6.5 | Operations, examinations and inspections | 36 |
| 6.5.1 | General | 36 |
| 6.5.2 | Detection of tread defects | 36 |
| 6.5.3 | Detection of thermal damage on the wheel rim or tyre | 37 |
| 6.5.4 | Detection of wheel tread roll-over | 37 |
| 6.5.5 | Detection of damage to chamfered corner and flange | 37 |
| 6.5.6 | Detection of damage resulting from identification markings | 37 |
| 6.5.7 | Detection of defects on the external and internal face of the rim | 37 |
| 6.5.8 | Verification of web integrity | 37 |
| 6.5.9 | Verification of hub integrity | 38 |
| 6.5.10 | Verification of rim integrity - Detection of deep sub-surface tread defects | 38 |
| 6.5.11 | Detection of thermal defects on the web of a wheel used as a braking surface | 38 |
| 6.5.12 | Detection of overheating affecting the wheel rim-web transition on monobloc wheels | 38 |
| 6.5.13 | Verification of axle surface integrity | 38 |
| 6.5.14 | Detection of damage caused by corrosion | 40 |
| 6.5.15 | Detection of circumferential defects around the whole circumference | 40 |
| 6.5.16 | Detection of circumferential defects in a singular section of the circumference | 40 |
| 6.5.17 | Detection of notches and impact damage | 41 |
| 6.5.18 | Detection of longitudinal defects on axles | 41 |
| 6.5.19 | Detection of damage in interference fit zones | 41 |
| 6.5.20 | Verification after rectification | 41 |
| 6.5.21 | Verification of residual magnetism | 41 |
| 6.5.22 | Lubrication operation | 41 |
| 6.5.23 | Checking for axle box defects | 41 |
| 6.5.24 | Verification of wheelset electrical resistance after heavy maintenance of boxed wheelsets | 41 |
| 6.6 | Requirements for additional maintenance equipment and operations | 42 |
| 7 | In-service boxed wheelset maintenance | 42 |
| 7.1 | Maintenance plan | 42 |
| 7.2 | Wheelset protection during vehicle and bogie cleaning | 42 |
| 8 | Off-vehicle wheelset maintenance | 42 |
| 8.1 | Maintenance plan | 42 |
| 8.2 | Key operations for off-vehicle wheelset maintenance | 43 |
| 8.3 | Off-vehicle boxed wheelset cleaning | 43 |
| 8.4 | NDT Interval | 43 |
| 9 | Action to be taken on any wheelset after an incident in service or when not covered by the maintenance plan | 44 |
| 9.1 | Wheelset bearings subject to water ingress | 44 |
| 9.2 | Wheelsets having been subjected to a short circuit current (e.g. from falling overhead line equipment, etc.) | 44 |
| 9.3 | Detection by a trackside facility of a wheel circularity defect | 44 |
| 9.4 | Wheelsets loaded over the allowed limit | 44 |
| 9.5 | Hot axle box detection | 45 |
| 9.5.1 | General | 45 |
| 9.5.2 | Technical procedure | 45 |
| 9.6 | Derailment | 45 |
| 9.7 | Head-on collision | 45 |
| 9.8 | Lubricant leakage or loss from the axle box | 46 |
| 9.9 | Brake incident (detection of seized brake or discoloration) | 46 |
| 9.10 | Reporting after detection of a wheelset irregularity outside the maintenance plan | 46 |
| 10 | Equipment not subject to Directive 2008/57/EC | 46 |
| 11 | Summary table of requirements of this standard | 46 |

| | |
|---|-----------|
| Annex A (normative) Minimum database content for freight wagon wheelset traceability | 47 |
| A.1 Data categories for storage time | 47 |
| A.2 Minimum data to be collected | 47 |
| A.2.1 Boxed wheelset | 47 |
| A.2.2 Wheelset axle | 49 |
| A.2.3 Wheels | 50 |
| A.2.4 Bearings | 51 |
| A.2.5 Medium and heavy wheelset maintenance | 51 |
| A.2.6 Vehicle in which the boxed wheelset is mounted (not applicable for bogies with variable gauge) and in-service incidents (since applying traceability system) | 52 |
| A.3 Measures to be applied resulting from lack of traceability | 52 |
| Annex B (informative) Database content for the tractability of wheelsets of vehicles in the scope of TSI "Rolling stock - Locomotive and passenger rated vehicles" (TSI Loc & Pas) | 54 |
| B.1 Data categories for storage time | 54 |
| B.2 Minimum data to be collected | 54 |
| B.2.1 Boxed wheelset | 54 |
| B.2.2 Axle | 56 |
| B.2.3 Wheels | 57 |
| B.2.4 Bearings | 58 |
| B.2.5 Medium and heavy wheelset maintenance | 58 |
| B.2.6 Vehicle in which the boxed wheelset is mounted (not applicable for bogies with variable gauge) and in-service incidents (since applying traceability system) | 59 |
| B.3 Measures to be applied resulting from lack of traceability | 60 |
| Annex C (normative) Definition and illustration of defects | 61 |
| C.1 General | 61 |
| C.2 Defects for all types of wheel | 61 |
| C.2.1 Wheel flat | 61 |
| C.2.2 Metal build-up | 62 |
| C.2.3 Shelling, cavities | 63 |
| C.2.4 Scaling | 63 |
| C.2.5 Tread indentation | 64 |
| C.2.6 Isolated transverse cracking | 64 |
| C.2.7 Circularity defect | 65 |
| C.2.8 Spalling (thermal effects due to tread braking) | 67 |
| C.2.9 Rolling contact fatigue | 68 |
| C.2.10 Thermal cracks | 68 |
| C.2.11 Wheel tread roll-over | 70 |
| C.2.12 Damage to chamfered corner | 70 |
| C.2.13 Wheel tread - grooves and channels (or smooth edged circumferential grooves and sharp edged circumferential fluting) | 71 |
| C.2.14 False flange | 72 |
| C.2.15 Damage on the flange | 74 |
| C.2.16 Sharp-edged radial marks and radial defects on the internal face of the rim (FIJ) | 75 |
| C.2.17 Damage resulting from identification markings | 76 |
| C.2.18 Damage from lathe driving tools | 77 |
| C.2.19 Sharp-edged circumferential defects on the web or wheel centre | 77 |
| C.2.20 Sharp-edged radial defect on the web | 78 |
| C.2.21 Wheel web hole defects | 78 |
| C.2.22 Cracks in the wheel hub | 79 |
| C.3 Defects specific to wheel types | 79 |
| C.3.1 Deep sub-surface tread defect on monobloc wheels | 79 |
| C.3.2 Wheel web defects on monobloc wheels | 80 |
| C.3.3 Exceptional thermomechanical stressing in tyred wheels | 82 |
| C.4 Axle defects | 82 |
| C.4.1 Axle protection defect - Damage on the painting/coating | 82 |
| C.4.2 Corrosion | 83 |
| C.4.3 Circumferential defects | 84 |

| | | |
|--|---|-----|
| C.4.4 | Notches and impact damage | 86 |
| C.4.5 | Longitudinal defects | 87 |
| C.4.6 | Damage in the interference fit zones | 87 |
| C.5 | Axle box defects | 88 |
| C.6 | Wheelset defects | 89 |
| C.6.1 | General | 89 |
| C.6.2 | Wheel distortion | 89 |
| C.6.3 | In service axial or angular movement of a wheel or of one of the other components | 90 |
| C.6.4 | Bent axle | 91 |
| Annex D (normative) Freight stock | | 92 |
| Annex E (informative) Rim size without roll-over for equipment not subject to Directive 2008/57/EC | | 93 |
| Annex F (normative) Definitions of Type A and B axles | | 94 |
| Annex G (informative) Permissible circularity defects | | 97 |
| Annex H (informative) Tyred wheels and resilient wheels | | 98 |
| H.1 | General | 98 |
| H.2 | Marking of tyred wheels and resilient wheels | 98 |
| H.2.1 | General | 98 |
| H.2.2 | Tyre thickness of tyred wheels | 99 |
| H.3 | Defects specific to tyred wheels | 100 |
| H.4 | Verification of the electrical resistance during medium and heavy maintenance | 101 |
| Annex I (normative) Reference images for axle surface condition limits for off vehicle wheelset maintenance | | 102 |
| I.1 | General | 102 |
| I.2 | Local and severe defect | 102 |
| I.3 | Large and heavily corroded areas, strongly and uniformly pitted surface | 103 |
| I.4 | Corrosion defects in abutment area and transition radii | 104 |
| Annex J (informative) NDT interval | | 105 |
| J.1 | General | 105 |
| J.2 | Axle | 105 |
| J.3 | Wheel | 105 |
| Annex K (informative) Summary of the requirements of this standard for in-service boxed wheelsets | | 106 |
| Annex L (informative) Characteristics of narrow gauge wheelsets | | 108 |
| Annex M (informative) Characteristics of Spanish and Portuguese gauge wheelsets | | 109 |
| Annex N (informative) Characteristics of Finnish and Baltic Country Gauge Wheelsets | | 110 |
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2008/57/EC aimed to be covered | | 111 |
| Bibliography | | 114 |